

Accessories for KZS



PS KZS-2M/4M is an auxiliary switch used for remote signalling of the RCBO to which it is fixed on the right side. PS KZS-2M/4M may also be fixed later of the state. Clamps are safe to touch. External dimensions comply with RCBO, built-in width is 0,5 module (9 mm). During fitting, the RCBO must be switched off.

The auxiliary switch can be used in combination with RCBOs manufactured after 1. 10. 2018. The production date is visible on the bottom of the product or above the test button. The number must be greater than 18401.

Auxiliary switch PS KZS-2M/4M				
Type	Code No.	contacts	Weight [g]	Packaging [pcs]
PS KZS-2M/4M	002159500	1xNC, 1xNC/NO	53	1/12

Residual current circuit breaker with integral overcurrent protection KZS-4M 2p B

Rated short-circuit capacity 10 kA	Rated current 6 - 40 A	Tripping characteristic B, C	Rated residual current 0,03 A - 0,3 A
--	----------------------------------	--	---

KZS-4M 2p B $I_{\Delta n} = 30 \text{ mA}$				
I_n [A]	Code No. B	Code No. C	Weight [g]	Packaging [pcs]
6	002174511	002174531	369	1/27
10	002174512	002174532	369	1/27
13	002174513	002174533	369	1/27
16	002174514	002174534	369	1/27
20	002174515	002174535	369	1/27
25	002174516	002174536	369	1/27
32	002174517	002174537	369	1/27
40	002174518	002174538	390	1/27



KZS-4M 2p B $I_{\Delta n} = 100 \text{ mA}$				
I_n [A]	Code No. B	Code No. C	Weight [g]	Packaging [pcs]
6	002174611	002174631	369	1/27
10	002174612	002174632	369	1/27
13	002174613	002174633	369	1/27
16	002174614	002174634	369	1/27
20	002174615	002174635	369	1/27
25	002174616	002174636	369	1/27
32	002174617	002174637	369	1/27
40	002174618	002174638	390	1/27

KZS-4M 2p B $I_{\Delta n} = 300 \text{ mA}$				
I_n [A]	Code No. B	Code No. C	Weight [g]	Packaging [pcs]
6	002174811	002174831	369	1/27
10	002174812	002174832	369	1/27
13	002174813	002174833	369	1/27
16	002174814	002174834	369	1/27
20	002174815	002174835	369	1/27
25	002174816	002174836	369	1/27
32	002174817	002174837	369	1/27
40	002174818	002174838	390	1/27