

dimmere pentru benzi cu led monoculare



05-0502
reglaj manual
aparent - 8A



05-0501
reglaj cu telecomanda(RF) - 8A
Telecomanda poate functiona cu mai
multe receptoare simultan



05-0500
reglaj manual sau
cu telecomanda (IR)
aparent sau ingropat - 8A



05-0503
reglaj manual
aparent - 16A



30-3380 / 30-3381
"TOUCH"
reglaj manual
ingropat - 8A



30-33325
"TOUCH"
reglaj cu telecomanda(RF) - 25A
Telecomanda poate functiona in paralel cu mai
multe receptoare simultan in functie de
setarile efectuate

COD dablerom	CURENT (A)	TENSIEUNE/PUTERE		DIMENSIUNI			PACK. (buc)
		1 (V)/(W)	2 (V)/(W)	L (mm)	W (mm)	h (mm)	
05-0502	8A	12V DC / 96W	24V DC / 192W	89	59	35	1/100
05-0501	8A	12V DC / 96W	24V DC / 192W	110	56	34	1/50
05-0500	8A	12V DC / 96W	24V DC / 192W	87	87	53	1/60
05-0503	16A	12V DC / 192W	24V DC / 384W	89	59	35	1/100
30-3380 alb	8A	12V DC / 96W	24V DC / 192W	80	80	42	1/60
30-3381 negru	8A	12V DC / 96W	24V DC / 192W	80	80	42	1/60
30-33325	25A	12V DC / 300W	24V DC / 600W	127	41	32	1/40

dimmere & controlere pentru benzi cu led RGB



05-050
reglaj cu
telecomanda(IR) - 6A



30-33324
"TOUCH"
reglaj cu telecomanda(RF) - 24A
Telecomanda poate functiona cu mai
multe receptoare simultan in functie de
setarile efectuate



05-057
reglaj cu telecomanda(IR) - 15A
se poate conecta cu consola DMX-512
se poate conecta la calculator



RGB



30-34124
RGB + ALB
reglaj cu telecomanda(RF) - 16A
Telecomanda poate functiona cu mai
multe receptoare simultan in functie de
setarile efectuate

COD dablerom	CURENT (A)	TENSIEUNE/PUTERE		DIMENSIUNI			PACK. (buc)
		1 (V)/(W)	2 (V)/(W)	L (mm)	W (mm)	h (mm)	
05-050	6A	12VDC / 72W(24W/iesire)	24VDC / 144W(48W/iesire)	35	25	20	1/100
30-33324	24A	12VDC / 288W(96W/iesire)	24VDC / 576W(192W/iesire)	83	81	33	1/30
05-057	15A	12VDC / 180W(60W/iesire)	24VDC / 360W(120W/iesire)	175	35	45	1/10
05-059		cablu adaptor DATA 1m cu RJ45 8P8C la stecher XLR3 pentru 05-057					1
30-341224	16A	12VDC / 192W(48W/iesire)	24VDC / 384W(96W/iesire)	77	61	22	1/60

amplificatoare pentru benzi cu led



30-3220
pt. BANDA LED MONOCOLORA



RGB
05-049
pt. BANDA LED RGB



RGB
05-04967
pt. BANDA LED RGB



COD dablerom	CURENT (A)	TENSIEUNE/PUTERE		DIMENSIUNI			PACK. (buc)
		1 (V)/(W)	2 (V)/(W)	L (mm)	W (mm)	h (mm)	
30-3220	20A	12VDC / 240W	24VDC / 480W	81	66	25	1/50
05-049	12A	12VDC / 144W(48W/iesire)	24VDC / 288W(96W/iesire)	98	45	18	1/100
05-04967	12A	12VDC / 144W(48W/iesire)	24VDC / 288W(96W/iesire)	95	52	30	1/50