


## benzi cu led - IP67



- Benzi LED SMD  
- Unghi de lumina la 120°



**4.8W/m - 12V - SMD:3528**

Prelungire max.: 10m

lumina ≈ 480lm/m



**IP67 CE**

| COD dablerom    | TENSIUNE (V) | PUTERE (W/m) | LUMINA   | LED (nr./m) | LED (tip) | DIMENSIUNI |   | TAIERE min. (mm) | PACK. (metri) |
|-----------------|--------------|--------------|----------|-------------|-----------|------------|---|------------------|---------------|
| 05-004/cald     | 12V DC       | 4.8W/m       | calda    | 60          | 3528      | 10         | 5 | 50               | 5/50          |
| 05-004/rece     | 12V DC       | 4.8W/m       | rece     | 60          | 3528      | 10         | 5 | 50               | 5/50          |
| 05-004/albastru | 12V DC       | 4.8W/m       | albastra | 60          | 3528      | 10         | 5 | 50               | 5/50          |



**7.2W/m - 12V - SMD:5050**

Prelungire max.: 10m

lumina ≈ 720lm/m



**IP67 CE**

| COD dablerom    | TENSIUNE (V) | PUTERE (W/m) | LUMINA   | LED (nr./m) | LED (tip) | DIMENSIUNI |   | TAIERE min. (mm) | PACK. (metri) |
|-----------------|--------------|--------------|----------|-------------|-----------|------------|---|------------------|---------------|
| 05-083/cald     | 12V DC       | 7.2W/m       | calda    | 30          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-083/rece     | 12V DC       | 7.2W/m       | rece     | 30          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-083/albastru | 12V DC       | 7.2W/m       | albastra | 30          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-083/RGB      | 12V DC       | 7.2W/m       | RGB      | 30          | 5050      | 12         | 5 | 100              | 5/50          |



**14.4W/m - 24V - SMD:5050**

Prelungire max.: 10m

lumina ≈ 1440lm/m



**IP67 CE**

| COD dablerom     | TENSIUNE (V) | PUTERE (W/m) | LUMINA   | LED (nr./m) | LED (tip) | DIMENSIUNI |   | TAIERE min. (mm) | PACK. (metri) |
|------------------|--------------|--------------|----------|-------------|-----------|------------|---|------------------|---------------|
| 05-0842/cald     | 24V DC       | 14.4W/m      | calda    | 60          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-0842/rece     | 24V DC       | 14.4W/m      | rece     | 60          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-0842/albastru | 24V DC       | 14.4W/m      | albastra | 60          | 5050      | 12         | 5 | 100              | 5/50          |
| 05-0842/RGB      | 24V DC       | 14.4W/m      | RGB      | 60          | 5050      | 12         | 5 | 100              | 5/50          |

## accesorii pentru benzi cu led


| COD dablerom | PENTRU BANDA (latimea) | (tip)      | PACK. (buc) |
|--------------|------------------------|------------|-------------|
| 05-30-31     | 8mm                    | monocolora | 10/1000     |
| 05-30-32     | 10mm                   | monocolora | 10/1000     |
| 05-30-33     | 10mm                   | RGB        | 10/1000     |
| 05-30-34     | 8mm                    | monocolora | 10/2000     |
| 05-30-35     | 10mm                   | monocolora | 10/2000     |
| 05-30-36     | 10mm                   | RGB        | 10/1000     |
| 05-30-37     | 8mm                    | monocolora | 10/1000     |
| 05-30-38     | 10mm                   | monocolora | 10/2000     |
| 05-30-39     | 10mm                   | RGB        | 10/2000     |
| 05-30-02     | 10mm                   | monocolora | 10          |
| 05-30-05     | 12mm                   | monocolora | 10          |
| 05-30-06     | 12mm                   | RGB        | 10          |
| 05-30-00     | 10mm                   |            | 25          |
| 05-30-03     | 12mm                   |            | 25          |



**05-30-31 / 05-30-32**  
element de alimentare



**05-30-33**



**05-30-34**  
**05-30-35**

**05-30-36**


conector (muta)



**05-30-37 / 05-30-35 conector**  
flexibil cu 2 mufe



**05-30-39**



capac pentru element de alimentare pentru banda

**05-30-02**  
**05-30-05**

**05-30-06**



sistem de prindere pentru banda led IP67

**05-30-00**

**05-30-03**

\* verificati temperatura de culoare inainte de montare

\* nu indoiti banda la unghi drept de 90°

