

## benzi cu led - IP54



~25000 ore  
de functionare



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



cu profil de aluminiu



IP54 CE



4.8W/m - 12V - SMD:3528  
Prelungire max.: 10m

lumina ≈ 480lm/m

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI		TAIERE min. (mm)	PACK. (metri)
05-34121/cald	12V DC	4.8W/m	calda	60	3528	8	3	50	5/50
05-34121/alb	12V DC	4.8W/m	alb	60	3528	8	3	50	5/50
05-34121/rece	12V DC	4.8W/m	rece	60	3528	8	3	50	5/50
05-34121/rosu	12V DC	4.8W/m	rosie	60	3528	8	3	50	5/50
05-34121/galben	12V DC	4.8W/m	galbena	60	3528	8	3	50	5/50
05-34121/albastru	12V DC	4.8W/m	albastru	60	3528	8	3	50	5/50



7.2W/m - 12V - SMD:5050  
Prelungire max.: 10m

lumina ≈ 720lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI		TAIERE min. (mm)	PACK. (metri)
05-081/cald	12V DC	7.2W/m	calda	30	5050	10	3	100	5/50
05-081/alb	12V DC	7.2W/m	alba	30	5050	10	3	100	5/50
05-081/rece	12V DC	7.2W/m	rece	30	5050	10	3	100	5/50
05-081/rosu	12V DC	7.2W/m	rosie	30	5050	10	3	100	5/50
05-081/albastru	12V DC	7.2W/m	albastru	30	5050	10	3	100	5/50
05-081/verde	12V DC	7.2W/m	verde	30	5050	10	3	100	5/50
05-081/RGB	12V DC	7.2W/m	RGB	30	5050	10	3	100	5/50
05-081/RGBW	12V DC	7.2W/m	RGB+alb	30	5050	10	3	170	5/50



14.4W/m - 12V - SMD:5050  
Prelungire max.: 5m

lumina ≈ 1440lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI		TAIERE min. (mm)	PACK. (metri)
05-0811/cald	12V DC	14.4W/m	calda	60	5050	10	3	50	5/50
05-0811/alb	12V DC	14.4W/m	alba	60	5050	10	3	50	5/50
05-0811/rece	12V DC	14.4W/m	rece	60	5050	10	3	50	5/50
05-0811/albastru	12V DC	14.4W/m	albastru	60	5050	10	3	50	5/50
05-0811/RGB	12V DC	14.4W/m	RGB	60	5050	10	3	50	5/50



14.4W/m - 24V - SMD:5050  
Prelungire max.: 10m

lumina ≈ 1440lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI		TAIERE min. (mm)	PACK. (metri)
05-084/cald	24V DC	14.4W/m	calda	60	5050	10	3	100	5/50
05-084/alb	24V DC	14.4W/m	alba	60	5050	10	3	100	5/50
05-084/rece	24V DC	14.4W/m	rece	60	5050	10	3	100	5/50
05-084/rosu	24V DC	14.4W/m	rosie	60	5050	10	3	100	5/50
05-084/galben	24V DC	14.4W/m	galbena	60	5050	10	3	100	5/50
05-084/albastru	24V DC	14.4W/m	albastru	60	5050	10	3	100	5/50
05-084/verde	24V DC	14.4W/m	verde	60	5050	10	3	100	5/50
05-084/RGB	24V DC	14.4W/m	RGB	60	5050	10	3	100	5/50
05-084/RGBW	24V DC	14.4W/m	RGB+alb	60	5050	10	3	100	5/50

- \* verificati temperatura de culoare inainte de montare
- \* nu indoiti banda la unghi drept de 90°

