


benzi cu led - IP20



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



cu profil de aluminiu



IP20 CE



4.8W/m - 12V - SMD:3528

Prelungire max.: 10m

lumina ≈ 480lm/m

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
05-34112/cald	12V DC	4.8W/m	calda	60 3528	8 2	50	5/50
05-34112/alb	12V DC	4.8W/m	alba	60 3528	8 2	50	5/50
05-34112/rece	12V DC	4.8W/m	rece	60 3528	8 2	50	5/50
05-34112/rosu	12V DC	4.8W/m	rosie	60 3528	8 2	50	5/50
05-34112/galben	12V DC	4.8W/m	galbena	60 3528	8 2	50	5/50
05-34112/albastru	12V DC	4.8W/m	albastra	60 3528	8 2	50	5/50



7.2W/m - 12V - SMD:5050

Prelungire max.: 10m

lumina ≈ 720lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
05-080/cald	12V DC	7.2W/m	calda	30 5050	10 2	100	5/50
05-080/alb	12V DC	7.2W/m	alba	30 5050	10 2	100	5/50
05-080/rece	12V DC	7.2W/m	rece	30 5050	10 2	100	5/50
05-080/rosu	12V DC	7.2W/m	rosie	30 5050	10 2	100	5/50
05-080/galben	12V DC	7.2W/m	galbena	30 5050	10 2	100	5/50
05-080/albastru	12V DC	7.2W/m	albastra	30 5050	10 2	100	5/50
05-080/verde	12V DC	7.2W/m	verde	30 5050	10 2	100	5/50
05-080/RGB	12V DC	7.2W/m	RGB	30 5050	10 2	100	5/50
05-080/RGBW	12V DC	7.2W/m	RGB+alb	30 5050	10 2	170	5/50



14.4W/m - 12V - SMD:5050

Prelungire max.: 5m

lumina ≈ 1440lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
05-34129/cald	12V DC	14.4W/m	calda	60 5050	10 2	50	5/50
05-34129/alb	12V DC	14.4W/m	alba	60 5050	10 2	50	5/50
05-34129/rece	12V DC	14.4W/m	rece	60 5050	10 2	50	5/50
05-34129/rosu	12V DC	14.4W/m	rosie	60 5050	10 2	50	5/50
05-34129/galben	12V DC	14.4W/m	galbena	60 5050	10 2	50	5/50
05-34129/albastru	12V DC	14.4W/m	albastra	60 5050	10 2	50	5/50
05-34129/verde	12V DC	14.4W/m	verde	60 5050	10 2	50	5/50
05-34129/RGB	12V DC	14.4W/m	RGB	60 5050	10 2	50	5/50



14.4W/m - 24V - SMD:5050

Prelungire max.: 10m

lumina ≈ 1440lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
05-34249/cald	24V DC	14.4W/m	calda	60 5050	10 2	100	5/50
05-34249/alb	24V DC	14.4W/m	alba	60 5050	10 2	100	5/50
05-34249/rece	24V DC	14.4W/m	rece	60 5050	10 2	100	5/50
05-34249/RGB	24V DC	14.4W/m	RGB	60 5050	10 2	100	5/50
30-34249019	24V DC	14.4W/m	RGB+alb	60 5050	10 2	170	5/50

- * verificati temperatura de culoare inainte de montare
- * nu indoiti banda la unghi drept de 90°

