



## Tuburi fără halogenuri și accesorii

**original.** Produsele din seria HFT®-combină avantajele materialelor fără halogenuri și a celor care nu propagă flacăra. Dezvoltarea acestor sisteme este un pionierat al firmei Dietzel Univolt®.

**sigur.** Sistemele noastre au o contribuție esențială la limitarea pagubelor în caz de incendiu acolo unde siguranța oamenilor și a bunurilor are cea mai mare prioritate.

**de avangardă.**

Produsele HFT®-corespund celor mai noi standarde de instalații și reprezintă o alternativă ideală pentru cabluri fără halogenuri de orice tip. Cu HFT® „Next Generation“ s-a lărgit aria de aplicabilitate în concordanță cu cerințele privind siguranța conform LSF0H.

## Halogenfree Conduits and Accessories

**genuine.** Only products of the HFT® series combine the advantages of halogenfree and flame retardant materials. Dietzel Univolt® has been the pioneer in the development of such systems.

**safe.** Where the safety of human lives and material assets has highest priority, our systems have an essential share in limiting the damages and consequences of fires.

**advanced.**

HFT® products comply with the most recent installation standards and ideally complement halogenfree cables of any kind. Additionally, HFT® 'Next Generation' provides scope for an extended range of applications with safety requirements according to LSF0H.

**HFSB, cot de cuplare mufat;** gri deschis (RAL 7035), negru (RAL 9005) sau alb (RAL 9010), pentru îmbinarea tuburilor pentru instalații electrice rigide în unghi de 90°

**HFSB, normal bend, slip type;** light grey (RAL 7035), black (RAL 9005) or white (RAL 9010), for the connection of rigid conduits in an angle of 90°



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				gri deschis light grey	negru black	alb white
HFSB 16	16,0	50	600	065 492	009 622	038 576
HFSB 20	20,0	25	300	065 493	009 623	038 577
HFSB 25	25,0	20	160	065 494	009 624	038 578
HFSB 32	32,0	1	50	065 495	009 625	038 579
HFSB 40	40,0	1	35	065 496	009 626	038 580
HFSB 50	50,0	1	20	065 497	009 627	038 581
HFSB 63	63,0	1	8	065 498	027 261	-

**HFS, colier de fixare în 2 puncte;** gri deschis (RAL 7035), negru (RAL 9005) sau alb (RAL 9010), pentru montarea cu șuruburi Ø 4mm

**HFS, saddle, with two fixing holes;** light grey (RAL 7035), black (RAL 9005) or white (RAL 9010), for mounting with screws Ø 4mm



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				gri deschis light grey	negru black	alb white
HFS 16	16,0	100	3200	080 811	020 832	041 831
HFS 20	20,0	50	1600	080 812	020 833	041 832
HFS 25	25,0	100	1600	080 813	020 834	041 833
HFS 32	32,0	100	800	080 814	020 835	041 834
HFS 40	40,0	50	400	080 815	020 836	041 835
HFS 50	50,0	50	400	080 816	020 837	041 836
HFS 63	63,0	25	200	080 817	020 838	-

**HFSBS, colier de fixare cu distanțier;** negru (RAL 9005) sau alb (RAL 9010)

**HFSBS, spacer bar saddle;** black (RAL 9005) or white (RAL 9010)



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				negru black	alb white	
HFSBS 16	16,0	100	2400	009 628	041 852	
HFSBS 20	20,0	50	1200	009 629	037 033	
HFSBS 25	25,0	50	1200	009 630	041 621	
HFSBS 32	32,0	50	600	009 631	041 853	
HFSBS 40	40,0	25	300	009 632	041 854	
HFSBS 50	50,0	25	200	009 633	041 855	