



RED



GREEN




BLUE




RGB



3000K



4200K



6400K



SINGLE CHIP

REN

081 001 0001

REN/RGB

081 001 0002



12V DC

WATERPROOF


- 12V DC
- Input Current: 2A (1 Roll/5m)
- 24W (1 Roll/5m)
- 1.440 lm, per 16ft reel
- Average Life: 30.000 Hrs
- Standart Length: 1m / 60 LED
- LED Type: 35x28 SMD
- LED View Angle: 120
- Package: 5 m / Roll
- PCB Color: White
- With 3M self-adhesive backing for easy installation




3 LEDs make a group and each group can be cut or extended in terms of the length of application



RED



GREEN




BLUE




RGB



3000K



4200K



6400K



SINGLE CHIP

NiL

081 002 0001

NiL/RGB

081 002 0002

12V DC

NON WATERPROOF

- 12V DC
- Input Current: 2A (1 Roll/5m)
- 24W (1 Roll/5m)
- 1.440 lm, per 16ft reel
- Average Life: 30.000 Hrs
- Standart Length: 1m / 60 LED
- LED Type: 35x28 SMD
- LED View Angle: 120
- Package: 5 m / Roll
- PCB Color: White
- With 3M self-adhesive backing for easy installation



3 LEDs make a group and each group can be cut or extended in terms of the length of application

