

Devices

White

Carbon Matt

1P special switches 250 V~



09052
NO 10 A,
cord-operated.
Depth: 24,7 mm



09052.CM
NO 10 A,
cord-operated.
Depth: 24,7 mm



09050
NO 10 A, with
lightable name-plate
- 2 modules.
Depth: 25,2 mm

Switches for roller blind controls 250 V~



09060
2P 10 AX 2-way
switch,
OFF-central.
Depth: 33,5 mm



09062
1P NO 10 A
2-interlocked
push buttons.
Depth: 29 mm



09060.CM
2P 10 AX 2-way
switch,
OFF-central.
Depth: 33,5 mm



09062.CM
1P NO 10 A
2-interlocked
push buttons.
Depth: 29 mm

Quid - Electronic relay modules and control unit modules for roller shutters



03996
Centralizable relay module, slat orientation, with relay outputs for $\cos\phi$ 0,6 motor 2 A 220-240 V~ 50/60 Hz, position saving, for backside or junction boxes installation



03997
Control unit module, 2 inputs for NO push button, 6 outputs for Quid roller shutter relay module (03996), 220-240 V~ 50/60 Hz power supply, for backside or junction boxes installation

Connected actuators for roller shutter - backside installation



03982
Actuator for 1 roller shutter with slat orientation and change-over relay output for $\cos\phi$ 0,6 motor 2 A 100-240 V~ 50/60 Hz, remote control, Bluetooth® wireless technology 5.0 for View Wireless mesh system and Zigbee 3.0



Dimmers**



09135.1
MASTER,
universal
09135.1.120
As above,
120 V~.
Depth: 41,5 mm



09153
100-500 W
push-push +
potentiometer,
230 V~.
Depth: 40 mm



***09146**
60-900 W
60-300 VA,
potentiometer,
230 V~.
Depth: 40 mm



09147
30-500 W
30-300 VA,
potentiometer,
120 V~.
Depth: 40 mm



09135.1.CM
MASTER,
universal
09135.1.120.CM
As above,
120 V~.
Depth: 41,5 mm



09153.CM
100-500 W
push-push +
potentiometer,
230 V~.
Depth: 40 mm



***09146.CM**
60-900 W
60-300 VA,
potentiometer,
230 V~.
Depth: 40 mm



09147.CM
30-500 W
30-300 VA,
potentiometer,
120 V~.
Depth: 40 mm