

Devices • Socket outlets

White	Carbon Matt
-------	-------------

Dimmer - controllable loads

Type DIMMER	UNIVERSAL							
	09135.1				09135.1.120			
	2-wire connection		3-wire connection		2-wire connection		3-wire connection	
LOADS	LE	TE	LE	TE	LE	TE	LE	TE
Incandescence	40 ÷ 400 W	40 ÷ 300 W	40 ÷ 400 W	40 ÷ 300 W	40 ÷ 400 W	40 ÷ 300 W	40 ÷ 400 W	40 ÷ 300 W
Compact fluorescent lamps (CFL)	10 ÷ 100 W max 5 lamps	10 ÷ 200 W max 10 lamps	10 ÷ 100 W max 5 lamps	10 ÷ 200 W max 10 lamps	10 ÷ 100 W max 5 lamps	10 ÷ 200 W max 10 lamps	10 ÷ 100 W max 5 lamps	10 ÷ 200 W max 10 lamps
LED	5 ÷ 100 W max 10 lamps	5 ÷ 200 W max 20 lamps	3 ÷ 100 W max 10 lamps	3 ÷ 200 W max 20 lamps	5 ÷ 100 W max 10 lamps	5 ÷ 200 W max 20 lamps	3 ÷ 100 W max 8 lamps	3 ÷ 200 W max 16 lamps
Electronic transformers for halogen lamps	40 ÷ 300 VA max 3 transformers type	40 ÷ 300 VA max 5 transformers type	40 ÷ 300 VA max 3 transformers type	40 ÷ 300 VA max 5 transformers type	40 ÷ 300 VA max 3 transformers type	40 ÷ 300 VA max 5 transformers type	40 ÷ 300 VA max 3 transformers type	40 ÷ 300 VA max 5 transformers type

Dimmer - controllable loads

Type DIMMER	STANDARD		
	09153 (with push-push switch and rotary potentiometer control)	09146 (with rotary potentiometer)	09147 (with rotary potentiometer)
Incandescence	100 - 500 W	60 - 900 W	30 - 500 W
Ferromagnetic transformers for halogen lamps		60 - 300 VA 230 V~, 50/60 Hz	30 - 300 VA 120 V~, 50/60 Hz

Infrared switches



09181
Lighting switch, NO 6 A 230 V~
relay output, 50/60 Hz.
Depth: 37 mm



09181.CM
Lighting switch, NO 6 A 230 V~
relay output, 50/60 Hz.
Depth: 37 mm

SICURY 2P+E Italian standard socket outlets 250 V~



09201
10 A,
P11.
Depth:
23,2 mm



09203
Bpresa 16 A,
P17/11.
Depth:
23,2 mm



09209
16 A, P30
- 2 modules.
Depth: 29,3 mm



09210
16 A, universal
- 2 modules.
Depth: 26,4 mm



09201.CM
10 A,
P11.
Depth:
23,2 mm



09203.CM
Bpresa 16 A,
P17/11.
Depth:
23,2 mm



09209.CM
16 A, P30
- 2 modules.
Depth: 29,3 mm



09210.CM
16 A, universal
- 2 modules.
Depth: 26,4 mm

SICURY 2P+E socket outlets 250 V~ - German standard



09208
16 A, German
- 2 modules.
Depth:
29,5 mm



09208.C
16 A, German,
with cover
- 2 modules.
Depth: 29,5 mm



09208.CM
16 A, German
- 2 modules.
Depth:
29,5 mm



09208.C.CM
16 A, German,
with cover
- 2 modules.
Depth: 29,5 mm