

Socket outlets • Signal reception socket outlets

White	Carbon Matt
-------	-------------

USB supply unit

<b>09292</b> 5 V 1,5 A, 1 USB-A, 120-240 V~ 50/60 Hz, Depth: 37 mm	<b>09292.C</b> 5 V 1,5 A, 1 USB-C, 120-240 V~ 50/60 Hz, Depth: 37 mm

<b>09292.CM</b> 5 V 1,5 A, 1 USB-A, 120-240 V~ 50/60 Hz, Depth: 37 mm	<b>09292.C.CM</b> 5 V 1,5 A, 1 USB-C, 120-240 V~ 50/60 Hz, Depth: 37 mm

Special socket outlets

	<b>09330</b> 2P 6 A 24 V (SELV), for 01620 plug. Depth: 25 mm
--	---

	<b>09330.CM</b> 2P 6 A 24 V (SELV), for 01620 plug. Depth: 25 mm
--	--

Phone socket outlets

<b>09320</b> RJ11, 6-position 4-contact (6/4). Depth: 33,6 mm	<b>09324</b> Israeli stan- dard, screw terminals. Depth: 33,4 mm

<b>09320.CM</b> RJ11, 6-position 4-contact (6/4). Depth: 33,6 mm	<b>09324.CM</b> Israeli stan- dard, screw terminals. Depth: 33,4 mm

Coaxial TV-RD-SAT 5-2400 MHz socket outlets (output Ø 9,5 mm male and F-type female)

<b>09300.01</b> Male, single connection 1 dB. Depth: 26,1 mm	<b>09300.10</b> Male, through-line 10 dB. Depth: 26,1 mm	<b>09302.01</b> Demix, male and F-type, single connection 1 dB - 2 modules. Depth: 22,1 mm

<b>09300.01.CM</b> Male, single connection 1 dB. Depth: 26,1 mm	<b>09300.10.CM</b> Male, through-line 10 dB. Depth: 26,1 mm	<b>09302.01.CM</b> Demix, male and F-type, single connection 1 dB - 2 modules. Depth: 22,1 mm

Coaxial TV-FM-SAT 5-2400 MHz socket outlets (3 outputs: Ø 9,5 mm male and female + F-type)

<b>09303</b> Single connection 1 dB - 2 modules. Depth: 22 mm

<b>09303.CM</b> Single connection 1 dB - 2 modules. Depth: 22 mm

Coaxial TV 40-862 MHz socket outlets (1 output: Ø 9,5 mm female) and F-type socket outlets

<b>*09313</b> Single connection. Depth: 29 mm	<b>09318</b> With F-type female connector. Depth: 9 mm

<b>*09313.CM</b> Single connection. Depth: 29 mm	<b>09318.CM</b> With F-type female connector. Depth: 9 mm