

Data sheet

ID	J...B AP
Description	distribution box
Colour	light grey, similar to RAL 7035

Norms: EN 60670-1/EN60670-22/EN60695-2-10/EN60754-1



Working temperature	Degree of protection (IP)	UV-Level
-5 to 60 °C	IP65	L3

Art. no.	Dimensions Ø/LxB x T	Small Package	Large Package
105 641	85 x 85 x 55 mm	5 pc	120 pc
105 643	100 x 100 x 60 mm	6 pc	90 pc
105 851	155 x 100 x 70 mm	1 pc	56 pc
105 852	200 x 155 x 85 mm	1 pc	20 pc

Further technical details

Details

Halogen free	True
Tackable	False
Number of inlets	7
Type of housing feed-through	Trimmable step membrane
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	True
Material	PP

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.