ARS 00, ARS 00 /100 mm, smartARS 00 pro, ARS 00/100mm pro - accessories

| Description | | Article No. | Picture |
|--|--------------------------|---------------|---------|
| M8 terminal screw, for connection of conductors with lug terminal (set - 3 pcs.) | | 53-082961-001 | |
| Busbar shroud (polycarbonate) for busbar system 185 mm, Width 50 mm, length 562 mm, thickness 3 mm | | 1361400006T | |
| Isolating pin for fixing the 50 mm busbar shroud, M8 (set – 2 pcs.) | | 1361400001T | |
| Distance sleeve for current t (Length 36 mm, outer diaminner diameter =12,5 mm) | | 1115718010T | |
| S-bridge clamp – fixed with 2 x M5 screw - for connection of conductors with cross-section 4 mm² up to 70 mm² (set – 3 pcs.) | | 53-002143-001 | |
| V-shape clamp — S-bridge clamp + V-shape saddle - for connection of sector-shaped conductors with cross-section 1,5 up to 70 mm ² (stranded) or 95 mm ² (solid) (set - 3 pcs.) | | 53-001462-001 | |
| Universal earthing device for ARS 00,1,2,3 | | 1115281041T | |
| V- clamp 25-120 SW. For connection of conductor with cross-section: | | 1119510008T | |
| 16 - 95 mm² | 16 - 95 mm² 🛞 | | |
| 25 - 120 mm ² | 25 - 120 mm ² | | |
| V- clamp HM-10-120. For connection of conductor with cross-section: | | 1119510077T | |
| 10 - 70 mm ² | 10 - 70 mm² 🛞 | | |
| 25 - 120 mm ² | 25 - 95 mm ² | | |
| Hooked clamps for installation of ARS on to busbar system without drilled holes. (set - 3 pcs.) | | 53-945361-011 | 2 |







ARS 00-1

ARS 00/100 mm





smartARS 00-1 pro ARS 00/100 mm pro

ARS 00/100 mm, ARS 00/100mm pro - accessories

| Description | Article No. | Picture |
|--|-------------|---------|
| Micro switch for fuse link cover position monitoring (0-1) of ARS 00/100mm | 1115296049 | 1/6 |
| Support angle for installation of busbar shroud | 1115281081T | |





ARS 00/100 mm ARS 00/100 mm pro





| Description | Article No. | Picture |
|--|---------------|---------|
| Busbar shroud (polycarbonate) for busbar system 185 mm, Width 100 mm, length 707 mm, thickness 2 mm | 1361400007T | |
| Isolating pin for fixing the 100 mm busbar shroud, M12 (set – 2 pcs.) | 1361400002T | |
| Terminal protective cover | 51-930272-011 | |
| Distance sleeve for current transformer APA-W12 Length 36 mm, outer diameter =22,5 mm, inner diameter =12,5 mm | 1115718010T | |
| Universal earthing device for: 00, 1, 2, 3 | 1115281041T | |
| Fuse link cover for ARS 2 with fuse link state indication and monitoring | 53-002331-001 | |
| Fuse link cover for ARS 3 with fuse link state indication and monitoring | 53-002331-002 | |
| Rotary cover 2V | 51-000487-001 | 3 3 |