














Table 109. RBP 000 pro - accessories

Description	Size	Article No.	Picture
Auxiliary contacts (microswitch) AC-15 $U_e$ 230 V~ $I_e$ 2,5 A DC-13 $U_e$ 230 V~ $I_e$ 0,3 A	000	1115296311T	
Microswitch shroud 1115296311T	000	51-946806-001	



RBK 000

Table 110. RBK 000 pro - accessories

Description	Size	Article No.	Picture
Feeding bridge 2 x RBK 000, 35 mm <sup>2</sup>	000	1119510055T	
Feeding bridge 3 x RBK 000, 35 mm <sup>2</sup>	000	1119510056T	
Feeding bridge 4 x RBK 000, 35 mm <sup>2</sup>	000	1119510057T	
Feeding bridge 5 x RBK 000, 35 mm <sup>2</sup>	000	1119510058T	
Feeding bridge 2 x RBK 000, 50 mm <sup>2</sup>	000	1119510059T	
Feeding bridge 3 x RBK 000, 50 mm <sup>2</sup>	000	1119510060T	
Feeding bridge 4 x RBK 000, 50 mm <sup>2</sup>	000	1119510061T	
Feeding bridge 5 x RBK 000, 50 mm <sup>2</sup>	000	1119510062T	
Feeding bridge RBK 000 25-95 mm <sup>2</sup> (1 set - 3 pcs.) for connection of conductor of cross-section 25-70 mm <sup>2</sup>  25-95 mm <sup>2</sup> 	000	1119510071T	
Auxiliary contacts (microswitch) AC-15 $U_e$ 230 V~ $I_e$ 2,5 A DC-13 $U_e$ 230 V~ $I_e$ 0,3 A	000	1115296311T	
Microswitch shroud 1115296311T	000	51-000148-001	
Additional terminal shroud „O” extends shroud length of 25 mm	000	51-930160-011	