

PANEL MOUNTING SOCKET OUTLETS, straight

- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP67

Panel Mounting Socket Outlet

- Screw terminals
- Flange 120 x 120 mm
- High-temperature-resistant contact carrier
- Kontex contact
- Nickel plated contacts
- Box terminals
- Protection degree IP67

| Ampere | Poles | 110V 50-60 Hz | | | 230V 50-60 Hz | | | 400V 50-60 Hz | | | 500V 50-60 Hz | | | 100-300Hz > 50V | | | 301-500Hz > 50V | | | Qty | g each |
|--------|-------|------------------|------|------|------------------|------|-------|------------------|-------|------|------------------|------|------|--------------------|------|------|--------------------|------|------|------|--------|
| | | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | | |
| 125 | 3 | 13445 | | | 13452 | | | | | | | | | | | | | | 5 | 930 | |
| 125 | 4 | | | | 13449 | | 13447 | | 13448 | | | | | | | | | | 5 | 1005 | |
| 125 | 5 | | | | | | 13451 | | | | | | | | | | | | 5 | 1125 | |

Products with PILOT please add "P" to the ref.no.



Fig.: Type 13451

| Ampere Poles | 125 3 | 125 4 | 125 5 |
|---------------|-------|-------|-------|
| a | 120.0 | 120.0 | 120.0 |
| b | 120.0 | 120.0 | 120.0 |
| c | 100.0 | 100.0 | 100.0 |
| d | 100.0 | 100.0 | 100.0 |
| e Ø | 6.5 | 6.5 | 6.5 |
| f | 21.0 | 21.0 | 21.0 |
| h | 50.0 | 50.0 | 50.0 |
| i | 117.0 | 117.0 | 117.0 |
| k | 129.0 | 129.0 | 129.0 |
| l Ø | 104.0 | 104.0 | 104.0 |
| m | 6.0 | 6.0 | 6.0 |
| Cond. mm² min | 25 | 25 | 25 |
| Cond. mm² max | 70 | 70 | 70 |

4 MB 55

Panel Mounting Socket Outlet

- Screw terminals
- Flange 130 x 130 mm
- High-temperature-resistant contact carrier
- Kontex contact
- Nickel plated contacts
- Box terminals
- Protection degree IP67

| Ampere | Poles | 110V 50-60 Hz | | | 230V 50-60 Hz | | | 400V 50-60 Hz | | | 500V 50-60 Hz | | | 100-300Hz > 50V | | | 301-500Hz > 50V | | | Qty | g each |
|--------|-------|------------------|------|------|------------------|------|-------|------------------|-------|------|------------------|------|------|--------------------|------|------|--------------------|--|---|------|--------|
| | | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | 3pol | 4pol | 5pol | | | | | |
| 125 | 3 | | | | 13434 | | | | | | | | | | | | | | 5 | 965 | |
| 125 | 4 | | | | 13442 | | 13435 | | 13515 | | | | | | | | | | 5 | 1040 | |
| 125 | 5 | | | | | | 13436 | | | | | | | | | | | | 5 | 1140 | |

Products with PILOT please add "P" to the ref.no.



Fig.: Type 13436

| Ampere Poles | 125 3 | 125 4 | 125 5 |
|---------------|-------|-------|-------|
| a | 130.0 | 130.0 | 130.0 |
| b | 130.0 | 130.0 | 130.0 |
| c | 104.0 | 104.0 | 104.0 |
| d | 104.0 | 104.0 | 104.0 |
| e Ø | 6.5 | 6.5 | 6.5 |
| f | 21.0 | 21.0 | 21.0 |
| h | 50.0 | 50.0 | 50.0 |
| i | 117.0 | 117.0 | 117.0 |
| k | 129.0 | 129.0 | 129.0 |
| l Ø | 104.0 | 104.0 | 104.0 |
| m | 1.0 | 1.0 | 1.0 |
| Cond. mm² min | 25 | 25 | 25 |
| Cond. mm² max | 70 | 70 | 70 |

4 MB 55