



















ARS 00, ARS 00/100 mm, smartARS 00 pro, ARS 00/100mm pro - accessories

Description	Article No.	Picture
M8 terminal screw, for connection of conductors with lug terminal (set - 3 pcs.)	53-082961-001	
Busbar shroud (polycarbonate) for busbar system 185 mm, Width 50 mm, length 562 mm, thickness 3 mm	1361400006T	
Isolating pin for fixing the 50 mm busbar shroud, M8 (set – 2 pcs.)	1361400001T	
Distance sleeve for current transformer APA-W10 (Length 36 mm, outer diameter = 22,5 mm, inner diameter = 12,5 mm)	1115718010T	
S-bridge clamp – fixed with 2 x M5 screw - for connection of conductors with cross-section 4 mm ² up to 70 mm ² (set – 3 pcs.)	53-002143-001	
V-shape clamp – S-bridge clamp + V-shape saddle - for connection of sector-shaped conductors with cross-section 1,5 up to 70 mm ² (stranded) or 95 mm ² (solid) (set - 3 pcs.)	53-001462-001	
Universal earthing device for ARS 00, 1, 2, 3	1115281041T	
V- clamp 25-120 SW. For connection of conductor with cross-section:	1119510008T	
16 - 95 mm ²  16 - 95 mm ² 		
25 - 120 mm ²  25 - 120 mm ² 		
V- clamp HM-10-120. For connection of conductor with cross-section:	1119510077T	
10 - 70 mm ²  10 - 70 mm ² 		
25 - 120 mm ²  25 - 95 mm ² 		
Hooked clamps for installation of ARS on to busbar system without drilled holes. (set - 3 pcs.)	53-945361-011	



ARS 00-1



ARS 00/100 mm





smartARS 00-1 pro



ARS 00/100 mm pro

ARS 00/100 mm, ARS 00/100mm pro - accessories

Description	Article No.	Picture
Micro switch for fuse link cover position monitoring (0-1) of ARS 00/100mm	1115296049	
Support angle for installation of busbar shroud	1115281081T	



ARS 00/100 mm



ARS 00/100 mm pro

PBS 00, PBS 00/100 mm - accessories

Description	Article No.	Picture
M8 terminal screw, for connection of conductors with lug terminal (set - 3 pcs.)	53-082961-001	
Busbar shroud (polycarbonate) for busbar system 185 mm, Width 50 mm, length 562 mm, thickness 3 mm	1361400006T	
Hooked clamps for installation on to busbar system without drilled holes. (set - 3 pcs.)	53-945361-011	
Isolating pin for fixing the 50 mm busbar shroud, M8 (set – 2 pcs.)	1361400001T	
Distance sleeve for current transformer APA-W10 (Length 36 mm, outer diameter =22,5 mm, inner diameter =12,5 mm)	1115718010T	
S-Bridge clamp – fixed with 2 x M5 screw - for connection of conductors with cross-section 4 mm ² up to 70 mm ² (set – 3 pcs.)	53-002143-001	
V-shape clamp – S-bridge clamp + V-shape saddle - for connection of sector-shaped conductors with cross-section 1,5 up to 70 mm ² (stranded) or 95 mm ² (solid) (set - 3 pcs.)	53-001462-001	
Universal earthing device for PBS 00, 1, 2, 3	1115281041T	
V- clamp HM-10-120. For connection of conductor with cross-section:	1119510077T	
10 - 70 mm ² 10 - 70 mm ²		
25 - 120 mm ² 25 - 95 mm ²		



PBS 00-V-0

PBS 00/100 mm

ACCESSORIES PBS

PBS 00/100 mm - accessories

Description	Article No.	Picture
Terminal shroud/adjusting shroud	53-945924-011	
Single adapter 100/185 enabling to install PBS 00/100 mm on busbar system 185 mm	1115281021	
Double adapter 100/185 enabling to install two PBS 00/100 mm units on busbar system 185 mm at perforation holes on busbar system every 100 mm	1115281022T	



PBS 00/100 mm