

Description	Article No.	Picture
Busbar shroud (polycarbonate) for busbar system 185 mm, Width 100 mm, length 707 mm, thickness 2 mm	1361400007T	
Isolating pin for fixing the 100 mm busbar shroud, M12 (set – 2 pcs.)	1361400002T	
Terminal protective cover	51-930272-011	
Distance sleeve for current transformer APA-W12 Length 36 mm, outer diameter =22,5 mm, inner diameter =12,5 mm	1115718010T	
Universal earthing device for: 00, 1, 2, 3	1115281041T	
Fuse link cover for ARS 2 with fuse link state indication and monitoring	53-002331-001	
Fuse link cover for ARS 3 with fuse link state indication and monitoring	53-002331-002	
Rotary cover 2V	51-000487-001	

Description	Article No.	Picture
V-clamp HS (steel) for connection of two conductors with cross-section 35-185 mm ²  35-240 mm ²  35-240 mm ²  35-300 mm ² 	1119510085T	
Hooked clamps for installation of PBS 1, 2, 3 on to busbar system without drilled holes (set - 3 pcs.)	1115281037T	
Busbar shroud (polycarbonate) for busbar system 185 mm, Width 100 mm, length 707 mm, thickness 2 mm	1361400007T	
Isolating pin for fixing the 100mm busbar shroud, M12 (set - 2 pcs.)	1361400002T	
Extended terminal shroud. For use with terminal shroud	51-930313-01	
Terminal protective cover	51-930272-011	
Distance sleeve for current transformer APA-W12 length 36 mm, outer diameter =22,5 mm, inner diameter =12,5 mm	115718010T	
Long terminal shroud	51-930271-021	
Fuse link shroud	51-836288-011	
Universal earthing device for ARS 00, 1, 2, 3	1115281041T	