

PANEL MOUNTING SOCKET OUTLETS, straight

- With screwless Quick-Connect technology
- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP44

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 75 x 75 mm
- Protection degree IP44

Ampere	Poles	110V 50-60 Hz			230V 50-60 Hz			400V 50-60 Hz			500V 50-60 Hz			100-300Hz > 50V			301-500Hz > 50V			Qty	each
		3pol 4h	4pol 4h	5pol 4h	3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	3pol 7h	4pol 7h	5pol 7h	3pol 10h	4pol 10h	5pol 10h	3pol 2h	4pol 2h	5pol 2h		
16	3	13685	13686	13687	13688	13689	13690	10	105												
16	4	13691	13692	13693	13694	13695	13696	10	120												
16	5	13697	13698	132001	13699	13700	13701	10	135												
32	3	13702	13703	13704	13705	13706	13707	10	165												
32	4	13708	13709	13710	13711	13712	13713	10	185												
32	5	13714	13715	132002	13716	13717	13718	10	220												



Fig.: Type 132001

Ampere	Poles	16	16	16	32	32	32
	3		4	5	3	4	5
a		75.0	75.0	75.0	75.0	75.0	75.0
b		75.0	75.0	75.0	75.0	75.0	75.0
c		60.0	60.0	60.0	60.0	60.0	60.0
d		60.0	60.0	60.0	60.0	60.0	60.0
e ø		5.5	5.5	5.5	5.5	5.5	5.5
f		7.0	7.0	7.0	8.0	8.0	8.0
h		35.5	35.5	35.5	50.0	50.0	50.0
i		50.0	50.0	51.0	60.0	60.0	60.0
k		74.0	84.0	91.0	94.0	94.0	102.0
l ø		45.0	45.0	55.0	60.0	60.0	60.0
m		8.0	12.0	16.0	17.0	17.0	22.0
Cond. mm² min		1.5	1.5	1.5	2.5	2.5	2.5
Cond. mm² max		4	4	4	10	10	10

4 MB 263

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 56 x 56 mm for 16A 3p, 60 x 60 mm for 16A 4p
- Protection degree IP44

Ampere	Poles	110V 50-60 Hz			230V 50-60 Hz			400V 50-60 Hz			500V 50-60 Hz			100-300Hz > 50V			301-500Hz > 50V			Qty	each
		3pol 4h	4pol 4h	5pol 4h	3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	3pol 7h	4pol 7h	5pol 7h	3pol 10h	4pol 10h	5pol 10h	3pol 2h	4pol 2h	5pol 2h		
16	3	13656	13661	13662	13663	13664	13665	13666	10	90											
16	4	13657	13658	13659	13660	13661	13662	13663	10	110											



Fig.: Type 13663

Ampere	Poles	16	16
	3		4
a		56.0	60.0
b		56.0	60.0
c		44.0	50 - 52
d		44.0	50 - 52
e ø		4.4	5.5
f		7.0	7.0
h		35.5	35.5
i		51.0	53.0
k		70.0	80.0
l ø		45.0	45.0
m		13.0	9.0
Cond. mm² min		1.5	1.5
Cond. mm² max		4	4

4 MB 101

Panel Mounting Socket Outlet Quick-Connect

- Screwless terminals
- Kontex contact
- Flange 62 x 62 mm for 16A 3p, 72 x 65 mm for 16A 4p and 5p
- Protection degree IP44

Ampere	Poles	110V 50-60 Hz			230V 50-60 Hz			400V 50-60 Hz			500V 50-60 Hz			100-300Hz > 50V			301-500Hz > 50V			Qty	each
		3pol 4h	4pol 4h	5pol 4h	3pol 6h	4pol 9h	5pol 9h	3pol 9h	4pol 6h	5pol 6h	3pol 7h	4pol 7h	5pol 7h	3pol 10h	4pol 10h	5pol 10h	3pol 2h	4pol 2h	5pol 2h		
16	3	13667	13673	13679	13668	13674	13680	13669	13675	13681	13670	13676	13682	13671	13677	13683	13672	13678	13684	10	95
16	4	13668	13674	13680	13669	13675	13681	13670	13676	13682	13671	13677	13683	13672	13678	13684	10	120			
16	5	13669	13675	13681	13670	13676	13682	13671	13677	13683	13672	13678	13684	10	130						



Fig.: Type 13681

Ampere	Poles	16	16	16
	3		4	5
a		62.0	72.0	72.0
b		62.0	65.0	65.0
c		47.0	52.0	52.0
d		47.0	52.0	52.0
e ø		5.5	5.5	5.5
f		7.0	7.0	7.0
h		35.5	35.5	35.5
i		51.0	53.0	53.0
k		70.0	80.0	85.0
l ø		45.0	45.0	55.0
m		10.0	9.0	13.0
Cond. mm² min		1.5	1.5	1.5
Cond. mm² max		4	4	4

4 MB 100