

Basic

Die-cast aluminum recessed spotlight with round seal. Suitable for the installation on plasterboard ceiling. Matt white finish; COB Chip on Board and SMD technology; available in different color temperatures 3000k and 4000k and with three different optics; CRI ≥ 80 ; front protection IP44 (after installation of the product); insulation class II; LED useful life 30.000 h L70B50.

IP44 Protection degree IP44.

Source	LED COB / SMD
Power	10W / 15W / 20W / 30W
Driver included	On/Off
Drivers available	1-10V / DALI / Push
MacAdam	SDCM ≤ 4
CCT	3000 K / 4000 K
CRI	≥ 80
LED life	30.000 h
Insulation class	II
IP	44
Material	Aluminum
Warranty	5 years




Kit Emergency - Page 818



Groove

IP20 CRI ≥80 30.000 h ALUMINUM




① 100 mm

0,220 Kg/0,0012 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
10 W	110°	890 Lm	3000 K	White	123974	18
		1000 Lm	4000 K	White	147666	18




① 150 mm

0,410 Kg/0,0023 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
20 W	110°	1550 Lm	3000 K	White	123998	24
		1750 Lm	4000 K	White	147673	24




① 205 mm

0,660 Kg/0,0036 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
30 W	110°	2450 Lm	3000 K	White	124018	30
		2800 Lm	4000 K	White	147680	30




① 100 x 100 mm

0,270 Kg/0,0012 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
10 W	110°	890 Lm	3000 K	White	123981	19




① 150 x 150 mm

0,540 Kg/0,0023 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
20 W	110°	1550 Lm	3000 K	White	124001	26



① 205 x 205 mm

0,850 Kg/0,0036 m³

LED SMD AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
30 W	110°	2450 Lm	3000 K	White	124025	33

