




## Sconce FRYZJA



### OPTICS



„S”

### DETAILED DESCRIPTION

INDEX	NAZWA NAME	WYMIARY / DIMENSIONS (cm)		ŹRÓDŁO ŚWIATŁA / SOURCE OF LIGHT			OPRAWA / FIXTURE			FUNDAMENT FOUNDATION
		H/h <sub>1</sub> /h <sub>2</sub>	w/S	W	lm	lm / W	W	lm	lm / W	
173-00..-000023	FRYZJA K	24/-	10x10	6	720	120	7,5	520	70	-

Data for: Ra > 80, 4000K, 700mA. Source of light and integrated control gear, replacement only by the manufacturer's service.



### PRODUCT DESCRIPTION

Universal fixture designed to illuminate passage-ways, highlight driveways, parking lots, yacht quays and to illuminate gardens, alleys and paths. Lampshade made of milky PMMA.

### TECHNICAL SPECIFICATIONS


Voltage	230 V
Source power / fixture	Recommended: Integrated 7,5 W/520 lm
Lifetime	70.000 h LB 80/20
Optics	<b>S</b>
Ambient temperature	-30 ÷ +45
Light color	4000 3000 *
Ingress Protection	<b>IP65</b>
Protection class	<b>I II</b> *
CE	Yes

\* choice

### MECHANICAL DATA

Foundation	-
Column/body material	Aluminium
Lampshade	PMMA
Metal color	<div style="display: flex; align-items: center;"> <div style="width: 20px; height: 20px; background-color: #f0f0f0; margin-right: 5px;"></div> White 9003  <div style="width: 20px; height: 20px; background-color: #808080; margin-right: 5px; margin-top: 5px;"></div> Grey 7043  <div style="width: 20px; height: 20px; background-color: #404040; margin-right: 5px; margin-top: 5px;"></div> Graphite 7016  <div style="width: 20px; height: 20px; background-color: #202020; margin-right: 5px; margin-top: 5px;"></div> Black 9005  <div style="border: 1px solid black; padding: 2px; margin-left: 10px; margin-top: 5px;"><b>RAL*</b></div> </div>

### ON ORDER



\*\* on special order