






ARIA




ARIA 48




ARIA 24



ARIA 25 COB



ARIA 32

OPTYKA
OPTICS

AS



ASW



ASP



S

METAL KOLOR
METAL COLORszary 7043
grey 7043grafitowy 7016
graphite 7016czarny 9005
black 9005na zamówienie
on request

RAL

index		wymiary/dimensions	źródło światła/source of light			oprawa/fixture			wiatr/wind	masa/weight
		L/B/H [cm]	W	lm	lm/W	W	lm	lm/W	m ²	kg
191-1111-000031	ARIA K 25 COB	59/38/120	23,5	4080	173	26	3100	123	0,10	—
195-1111-000005	ARIA 24	38/38/70	24	3700	153	30	2700	90	0,10	4
195-1111-000007	ARIA 32	38/38/70	32	4800	150	36	3200	89	0,10	4
195-1111-000006	ARIA 48	38/38/70	48	7400	153	60	5400	90	0,10	4
195-1111-000083	ARIA 25 COB	38/38/70	23,5	4080	173	26	3100	123	0,10	4
195-1111-000084	ARIA BIS 24	38/38/62	24	3700	153	30	3240	108	0,06	3,5
195-1111-000085	ARIA BIS 32	38/38/62	32	4800	150	36	3850	107	0,06	3,5
195-1111-000086	ARIA BIS 48	38/38/62	48	7400	153	60	6480	108	0,06	3,5
191-1111-000087	ARIA BIS 25 COB	38/38/62	23,5	4080	133	26	3500	140	0,06	3,5
195-1111-000009	ARIA PLUS 48	57/57/72	48	7400	153	60	6500	108	0,06	6
195-1111-000008	ARIA PLUS 72	57/57/72	72	11100	153	90	10000	111	0,06	6

L — długość / lenght B — szerokość / width H — wysokość / height

Przybliżone dane w tabelach na 2022 rok. Dokładne dane dostępne w specyfikacjach.
Approximated data for 2022 in tables. Exact data available in specifications.

ARIA

by ELMARCO

ARIA

Klasyczna oprawa przystosowana do mocowania bezpośrednio na słupie o średnicy 60 mm lub systemie ramion — Aria, Aria Bis na wysokości 3–4 m, Aria Plus na wysokości 5–6 m.

Aluminiowy korpus stanowi szczelną komorę osprzętu zamkniętą płytą, na której od strony klosza zamontowany jest szczelny moduł LED z soczewką. Kopuła osadzona jest na ukształtowanych profilach połączonych z dolną rozetą, która pełni funkcję mocowania oprawy na słupie.

Wersja Aria posiada klosz z poliwęglanu odpornego na UV.

Wersja Aria Bis i Aria Plus bez klosza.

Przeznaczenie: oświetlenie przestrzeni o historycznym i sakralnym charakterze, a także parków, skwerów.

Classic fixture adapted for mounting directly at a post with 60mm diameter or in arm-system — Aria, Aria Bis at a height of 3–4 m, Aria Plus at a height of 5–6 m.

Aluminum body forms a sealed chamber for fittings closed with a plate and a sealed tight LED module (with the lens) attached to it at the lamp-shade's side. The chamber is seated on shaped profiles connected to its lower rosette, which serves as a mounting for the fixture on a post.

Aria version made of polycarbonate being resistant to UV radiation.

Aria Bis and Aria Plus version without lamp-shade.

Designed for: illumination of historical and sacred sites as well as parks, squares.




ARIA BIS




ARIA PLUS


ARIA BIS 24




ARIA PLUS 48




ARIA BIS 32



ARIA PLUS 72



ARIA BIS 25 COB



STANDARD

IP 65	CLASS I/II	CE	RECYCLE	ENERGY D	IK 08	4000°K 700 mA	CRI ≥70 ≥80
złącze IP 55 connection box IP 55	do wyboru optional				szkło IK 07 glass IK 07		do wyboru optional

NA ZAMÓWIENIE / ON REQUEST

DIM	2700°K — 5000°K	300 mA — 1050 mA	10 kV
------------	------------------------------	-------------------------------	--------------

