


downlight LED patrat incastrat - Slim Line




12W - 18W - 24W

- Corp de iluminat cu montaj incastrat
- Material :
 - carcasa din aluminiu
 - reflector din aluminiu
 - dispersor mat din P.C.
- Putere maxima - 12W/18W/24W
- Sistem de pornire inclus
- Tip LED: SMD



alb



COD		CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)	
dablerom	prodicator					D (mm)	h (mm)	Ø (mm)		
06-1220000	21-01220000	alb	12W	calda	3000k	1150	170x170	23	155x155	1/26
06-12200	21-0122001	alb	12W	alba	4000k	1150	170x170	23	155x155	1/26
06-122000	21-0122000	alb	12W	rece	6300k	1150	170x170	23	155x155	1/26
06-1820000	21-01820000	alb	18W	calda	3000k	1700	225x225	23	205x205	1/24
06-18200	21-0182001	alb	18W	alba	4000k	1700	225x225	23	205x205	1/24
06-182000	21-0182000	alb	18W	rece	6300k	1700	225x225	23	205x205	1/24
21-02521000		alb	24W	calda	3000k	2250	225x225	23	205x205	1/24
21-0252101		alb	24W	alba	4000k	2250	225x225	23	205x205	1/24
21-0252100		alb	24W	rece	6300k	2250	225x225	23	205x205	1/24
06-2520000	21-02520000	alb	24W	calda	3000k	2250	295x295	23	276x276	1/14
06-25200	21-0252001	alb	24W	alba	4000k	2250	295x295	23	276x276	1/12
06-252000	21-0252000	alb	24W	rece	6300k	2250	295x295	23	276x276	1/12

accesorii pentru downlight ST & PT cu LED

COD	DENUMIRE	PACK. (buc)
21-006	driver pt. downlight LED 6W-intrare:100-240VAC / iesire:12-27VDC 300mA	1
21-0012	driver pt. downlight LED 12W-intrare:100-240VAC / iesire:22-43VDC 300mA	1
21-0018	driver pt. downlight LED 18W-intrare:100-240VAC / iesire:40-60VDC 300mA	1
21-002518	driver pt. downlight LED 24W(D:220mm)-intr.:100-240VAC / ies.:16-56VDC 400mA	1
21-0025	driver pt. downlight LED 24W(D:300mm)-intr.:100-240VAC / ies.:65-85VDC 300mA	1
21-0129	driver dimabil pt. downlight LED 12W-intr.:180-265VAC / ies.:24-42VDC 300mA	1
21-0189	driver dimabil pt. downlight LED 18W-intr.:180-265VAC / ies.:30-63VDC 300mA	1
21-0259	driver dimabil pt. downlight LED 24W-intr.:180-265VAC / ies.:50-80VDC 300mA	1
21-09	convertor cu acumulator pt. corp LED de la 10W pana la 50W scoate 9W autonomia:3h / timp de incarcare minim 24h / cu test buton Intrare:90-280VAC / Iesire:12-90VDC 300mA / Baterie:Li-ion 7,2V 4400mAh	1/28