

## plafoniere LED cu senzor de miscare - IP54



# IP54



- Corp de iluminat cu montaj aparent
- Material : dispersor mat din P.C.
- Putere maxima : 15-18W



**ovală**  
15W



**rotundă**  
18W

**unghi detectie: 360°**  
**distanța detectie max.: 5m**  
**se activeaza la intuneric**  
**si ramane aprinsa: 2min.**



**A NU SE MONTA LA O DISTANTA MAI MICA DE 5metri, UNA FATA DE CEALALTA**

| COD          | MODEL  | CULOARE | PUTERE<br>(W) | LUMINA | LUMEN<br>(lm) | DIMENSIUNI |        |        | PACK.<br>(buc) |      |
|--------------|--------|---------|---------------|--------|---------------|------------|--------|--------|----------------|------|
|              |        |         |               |        |               | L (mm)     | W (mm) | h (mm) |                |      |
| 21-240157108 | OVAL   | alb     | 15W           | alba   | 4000k         | 1500       | 240    | 170    | 78             | 1/20 |
| 21-200187108 | ROTUND | alb     | 18W           | alba   | 4000k         | 1800       | 200    | -      | 55             | 1/20 |

## plafoniere LED cu senzor de prezenta - IP54



# IP54



- Corp de iluminat cu montaj aparent
- Material : dispersor mat din P.C.
- Putere maxima : 12-18W



**ovală**  
18W



**rotundă**  
18W

**unghi detectie: 360°**  
**distanța detectie max.: 5m**  
**se activeaza la intuneric**  
**si ramane aprinsa: 2min.**



**A NU SE MONTA LA O DISTANTA MAI MICA DE 5metri, UNA FATA DE CEALALTA**


| COD         | MODEL  | CULOARE | PUTERE<br>(W) | LUMINA | LUMEN<br>(lm) | DIMENSIUNI |        |        | PACK.<br>(buc) |      |
|-------------|--------|---------|---------------|--------|---------------|------------|--------|--------|----------------|------|
|             |        |         |               |        |               | L (mm)     | W (mm) | h (mm) |                |      |
| 21-26018710 | OVAL   | alb     | 18W           | alba   | 4000k         | 1800       | 260    | 135    | 58             | 1/18 |
| 21-20018710 | ROTUND | alb     | 18W           | alba   | 4000k         | 1800       | 200    | -      | 54             | 1/12 |

## plafoniere cu LED CCT si cu senzor de prezenta - IP40




**unghi detectie: 360°**  
**distanța detectie max.: 5m**  
**se activeaza la intuneric**  
**si ramane aprinsa: 2min.**

**CCT**



- Corp de iluminat cu montaj aparent
- Material : Policarbonat PC
- Intrupator pentru reglarea Intensitatii : 16W sau 20W sau 24W
- Intrupator pentru selectarea Luminii: Cald sau Alb sau Rece
- Sistem de pornire inclus



**A NU SE MONTA LA O DISTANTA MAI MICA DE 5metri, UNA FATA DE CEALALTA**

| COD        | CULOARE | PUTERE (W)   | LUMINA                    | DIMENSIUNI |        |        | PACK. (buc) |
|------------|---------|--------------|---------------------------|------------|--------|--------|-------------|
|            |         |              |                           | D (mm)     | h (mm) | Ø (mm) |             |
| 21-2832408 | alb     | 16W (1600lm) |                           |            |        |        |             |
|            |         | 20W (2000lm) | 3000k sau 4000k sau 6500k | 283        | 20     | -      | 1/10        |
|            |         | 24W (2400lm) |                           |            |        |        |             |
| 21-2832418 | negru   | 16W (1600lm) |                           |            |        |        |             |
|            |         | 20W (2000lm) | 3000k sau 4000k sau 6500k | 283        | 20     | -      | 1/10        |
|            |         | 24W (2400lm) |                           |            |        |        |             |