## Arca

Extruded aluminum linear system compatible with a wide range of lighting fittings with mechanical fixing. The system is anodized and varnished. It is available in black color and for different kind of installations: ceiling, suspension, or flush in plasterboard ceilings. Modules can be assembled according to the desired arrangement. The body section for the ceiling and suspension versions is 42 mm wide and 85 mm high, while the body for recessed version is 86 mm wide and 90 mm high. Both models are available in two lengths: 1000 mm and 3000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with UGR control lower than 13, the TRACK or PENDANT modules for SPOT illumination with different emission angles. The CORNER module for angle composition. Integrated LEDs, possibility of color temperature of 3000 K or 4000 K; starting binning ≤3-Step MacAdam; IP20 protection; insulation class III; LED useful life 50.000 h L70B50. The 48Vdc power supply gives great versatility and safety, with reversible settlement that can be modified if necessary. The system is suitable for environments where professional lighting with minimal design is required, such as OFFICES and SHOPS.

PRO

High-tech product with high quality materials, intended for professional use.



Product with UGR <13, <16 (Accent, Pendant).

Source LED COB / SMD

Driver includedNoDrivers availableOn/OffMacAdamSDCM 3

CCT 3000K/4000K

CRI ≥80

UGR <13, <16 (Accent, Pendant)

LED life 50.000h

Insulation class III
IP 20


Material Aluminum
Warranty 5 years



## **Arca Accent**

## LED SMD OSRAM CRI≥90- UGR <13






Power	Beam	Flux	CCT	Finish	Code	€
15 W	35°	1700 Lm	3000 K	Black	222929	134
		1850 Lm	4000 K	Black	223001	134

0,440 Kg/0,0026 m<sup>3</sup>


## LED SMD OSRAM CRI≥90- UGR <13





Power	Beam	Flux	CCT	Finish	Code	€
29 W	35°	3200 Lm	3000 K	Black	222936	230
		3400 Lm	4000 K	Black	223018	230

0,700 Kg/0,0087 m<sup>3</sup>



CRI≥90 15W 35° 1700Lm 3000K

90°	90°
60°	60°
30°	30°

m	lx	øm
1	4826	0,60
2	1207	1,21
3	536	1,81
4	301	2,42
5	193	3,02

CRI≥90 29W 35° 3200Lm 3000K







Arca Accent 300 mm



Arca Accent 600 mm

