

Arca

Extruded aluminum linear system compatible with a wide range of lighting fittings with mechanical fixing. The system is anodized and varnished. It is available in black color and for different kind of installations: ceiling, suspension, or flush in plasterboard ceilings. Modules can be assembled according to the desired arrangement. The body section for the ceiling and suspension versions is 42 mm wide and 85 mm high, while the body for recessed version is 86 mm wide and 90 mm high. Both models are available in two lengths: 1000 mm and 3000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with UGR control lower than 13, the TRACK or PENDANT modules for SPOT illumination with different emission angles. The CORNER module for angle composition. Integrated LEDs, possibility of color temperature of 3000 K or 4000 K; starting binning ≤ 3 -Step MacAdam; IP20 protection; insulation class III; LED useful life 50.000 h L70B50. The 48Vdc power supply gives great versatility and safety, with reversible settlement that can be modified if necessary. The system is suitable for environments where professional lighting with minimal design is required, such as OFFICES and SHOPS.


PRO High-tech product with high quality materials, intended for professional use.

UGR Product with UGR <13, <16 (Accent, Pendant).

Source	LED COB / SMD
Driver included	No
Drivers available	On/Off
MacAdam	SDCM 3
CCT	3000K / 4000K
CRI	≥ 80
UGR	<13, <16 (Accent, Pendant)
LED life	50.000h
Insulation class	III
IP	20
Material	Aluminum
Warranty	5 years




Arca Wide



0,410 Kg/0,0025 m³

LED SMD SAMSUNG


Power	Beam	Flux	CCT	Finish		Code	€
13W	98°	1950 Lm	3000 K	Black		222943	80
		2100 Lm	4000 K	Black		223025	80



0,700 Kg/0,0087 m³


LED SMD SAMSUNG

Power	Beam	Flux	CCT	Finish		Code	€
25W	98°	4000 Lm	3000 K	Black		222950	118
		4300 Lm	4000 K	Black		223032	118



m	lx	ø m
1	203	2,16
2	50	4,33
3	22	6,50
4	12	8,66
5	8	10,83

CRI≥80 13W 98° 1950Lm 3000K



m	lx	ø m
1	440	2,14
2	110	4,28
3	48	6,42
4	27	8,56
5	17	10,70

CRI≥80 25W 98° 4000Lm 3000K



Arca Wide 300 mm



Arca Wide 600 mm

