

Fox new

Cylindrical aluminum projector suitable for installation on three-phase track. White or black powder coating, 275 ° rotating head and 90 ° adjustable, the power driver is included and is located in the cylindrical body of the projector itself; light source with integrated LED COB technology, available with a color temperature of 3000K or 4000K and with color rendering index up to ≥ 80 ; starting binning ≤ 2 -Step MacAdam; asymmetric optics with medium aperture beam. Assembly and disassembly without tools. IP 20 protection; insulation class I; LED useful life 30.000 h L70B50. Perfect for lighting the small and medium size environments that require wide flexibility for arrangement, where great flexibility and color rendering is required, such as COMMERCIAL and RETAIL spaces, and an optimal performance-price ratio.

Source	LED COB
Power	8W / 15W / 25W
Driver included	On/Off
Drivers available	No
Track	Three-phase (standar Eutrac)
MacAdam	SDCM2
CCT	3000 K / 4000 K
CRI	≥ 80
LED life	30.000 h
Insulation class	I
IP	20
Material	Aluminum
Warranty	5 years




[Link - Page 620](#)



Glim Track

IP20 ALUMINUM




0,320 Kg/0,0180 m³

GU10 Bulbs LED GU10 13W 3000 K included. Code **189031**

Power	Finish		Code	€
max 50W	White		229676	59
	Black		229683	59



P. 314



0,290 Kg/0,0016 m³

GU10 Bulbs LED GU10 5W 3000 K included. Code **108292**

Power	Finish		Code	€
max 50W	White		229652	35
	Black		229669	35



SINGLE CONNECTION

Included	Required	Driver	Finish		Code	€
No	No	On/Off	White		170145	21
			Black		170152	21



Link - Page 620