

# Fox new

Cylindrical aluminum projector suitable for installation on three-phase track. White or black powder coating, 275 ° rotating head and 90 ° adjustable, the power driver is included and is located in the cylindrical body of the projector itself; light source with integrated LED COB technology, available with a color temperature of 3000K or 4000K and with color rendering index up to  $\geq 80$ ; starting binning  $\leq$  2-Step MacAdam; asymmetric optics with medium aperture beam. Assembly and disassembly without tools. IP 20 protection; insulation class I; LED useful life 30.000 h L70B50. Perfect for lighting the small and medium size environments that require wide flexibility for arrangement, where great flexibility and color rendering is required, such as COMMERCIAL and RETAIL spaces, and an optimal performance-price ratio.


Source	LED COB
Power	8W / 15W / 25W
Driver included	On/Off
Drivers available	No
Track	Three-phase (standar Eutrac)
MacAdam	SDCM2
CCT	3000 K / 4000 K
CRI	$\geq 80$
LED life	30.000 h
Insulation class	I
IP	20
Material	Aluminum
Warranty	5 years



[Link - Page 620](#)

# Spot Track

IP20 ALUMINUM



0,250 Kg/0,0016 m<sup>3</sup>

GU10 Not included - Recommended bulb 108292


Power	Finish		Code	€
max 50W	White		229706	33
	Black		229720	33



P. 312 P. 404

# Mouse Track

IP20 ALUMINUM



0,300 Kg/0,0027 m<sup>3</sup>

GU10 Not included - Recommended bulb 108292


Power	Finish		Code	€
max 50W	White		229768	33
	Black		229782	33



P. 312 P. 404

# Lunare Track

IP20 ALUMINUM



0,260 Kg/0,0060 m<sup>3</sup>

GU10 Not included - Recommended bulb 108292

Power	Finish		Code	€
max 28W	White		229737	33
	Black		229751	33



P. 406



SINGLE CONNECTION

Included	Required	Driver	Finish	Code	€
No	No	On/Off	White	170145	21
			Black	170152	21



Link - Page 620

