

Game ^{new}

Die-cast aluminum recessed spotlight with round or square seal, suitable for the installation on plasterboard ceilings. Matt chrome finish, matt white RAL 9001, matt black RAL 9011, matt gold RAL 1032. COB-Chip on Board technology for maximum efficiency; available with color temperatures 3000 K or 4000 K; CRI \geq 85. Assembling and disassembling without utensils; protection IP20; insulation class II; LED useful life 30.000 h L70B50. It can be dimmed with 1-10V and DALI.



Product with UGR <19.


Source	LED COB
Power	11W
Driver included	On/Off
Drivers available	1-10V / DALI
CCT	3000 K / 4000 K
CRI	\geq 85
UGR	<19
LED life	30.000 h
Insulation class	II
IP	20
Material	Aluminum
Warranty	5 years





Virus

□ IP20 CRI ≥ 90 30.000 h ALUMINUM




⌀ 30 mm

0,070 Kg/0,0003 m³

LED SMD OSRAM AND DRIVER Included

Power	Beam	Flux	CCT	Finish	Code	€
3W	20°	210 Lm	3000 K	White +	244808	25
				Gold +	244822	25
				Black +	244846	25
				Gold +	244853	25



m	lx	ø m
1	1374	0,30
2	344	0,60
3	153	0,91
4	86	1,20
5	55	1,50

CRI ≥ 90 3W 20° 210Lm 3000K



244808



244822



244846



244853