

Ego new

Linear system composed of extruded aluminum profile and lighting elements with magnetic fixing and mechanical safety lock. The system is powder coated and available in black color for ceiling, suspended or recessed installation. The modules can be assembled according to the desired layout. The profile section is 26 mm wide and 27 mm or 52 mm high. Available in two lengths: 1000 mm and 2000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with glare control (UGR < 19), the TRACK SINGLE or DOUBLE module for spot illumination with different angles of emission, and the PENDANT TUBE and WALL WASHER modules for an accented illumination. Integrated LED with color temperature of 3000k and CRI 90; IP20 protection, insulation class III; LED useful life 50.000 h L70B50. The 48 Vdc power supply guarantees great versatility and safety, the compositions are in fact reversible and modifiable if necessary. Suitable for the installation in large environments where great flexibility and color rendering is required, such as MUSEUMS, COMMERCIAL, RESIDENTIAL and RETAIL spaces.

PRO

High-tech product with high quality materials, intended for professional use.


UGR

Product with UGR < 19 (Accent, Pendant).

| | |
|--------------------------|-----------------------|
| Source | LED COB / SMD |
| Driver included | No |
| Drivers available | On/Off |
| MacAdam | SDCM 3 |
| CCT | 3000K |
| CRI | ≥90 |
| UGR | <19 (Accent, Pendant) |
| LED life | 50.000h |
| Insulation class | III |
| IP | 20 |
| Material | Aluminum |
| Warranty | 5 years |




Ego Accent



LED SMD OSRAM UGR <19

| Power | Beam | Flux | CCT | Finish | Code | € |
|-------|------|--------|--------|--------|--------|-----------------------|
| 7W | 35° | 750 Lm | 3000 K | Black | 257792 | 90 <small>new</small> |


0,140 Kg/0,0015 m³



LED SMD OSRAM UGR <19

| Power | Beam | Flux | CCT | Finish | Code | € |
|-------|------|---------|--------|--------|--------|------------------------|
| 13W | 35° | 1500 Lm | 3000 K | Black | 257686 | 130 <small>new</small> |

0,210 Kg/0,0019 m³




LED SMD OSRAM UGR <19

| Power | Beam | Flux | CCT | Finish | Code | € |
|-------|------|---------|--------|--------|--------|------------------------|
| 13W | 35° | 1500 Lm | 3000 K | Black | 257846 | 160 <small>new</small> |



0,470 Kg/0,0031 m³



| m | lx | øm |
|---|------|------|
| 1 | 3121 | 0,61 |
| 2 | 780 | 1,20 |
| 3 | 347 | 1,80 |
| 4 | 195 | 2,40 |
| 5 | 125 | 3,00 |

CRI≥90 13W 35° 1500Lm 3000K



Ego Accent 192 mm



Ego Accent 284 mm

