Ego new

Linear system composed of extruded aluminum profile and lighting elements with magnetic fixing and mechanical safety lock. The system is powder coated and available in black color for ceiling, suspended or recessed installation. The modules can be assembled according to the desired layout. The profile section is 26 mm wide and 27 mm or 52 mm high. Available in two lengths: 1000 mm and 2000 mm. Possibility of assembly with different source modules: the WIDE diffusing module, the ACCENT module with glare control (UGR < 19), the TRACK SINGLE or DOUBLE module for spot illumination with different angles of emission, and the PENDANT TUBE and WALL WASHER modules for an accented illumination. Integrated LED with color temperature of 3000k and CRI 90; IP20 protection, insulation class III; LED useful life 50.000 h L70B50. The 48 Vdc power supply guarantees great versatility and safety, the compositions are in fact reversible and modifiable if necessary. Suitable for the installation in large environments where great flexibility and color rendering is required, such as MUSEUMS, COMMERCIAL, RESIDENTIAL and RETAIL spaces.

PRO

High-tech product with high quality materials, intended for professional use.



Product with UGR <19 (Accent, Pendant).

Source LED COB / SMD

Driver includedNoDrivers availableOn/OffMacAdamSDCM 3CCT3000KCRI≥90

UGR <19 (Accent, Pendant)

LED life 50.000h


Insulation class III IP 20

Material Aluminum
Warranty 5 years



Ego Track Single






0,080 Kg/0,0041 m³

LED SMD OSRAM

Power	Beam	Flux	CCT	Finish	Code	€	
3W	30°	230 Lm	3000 K	Black	257617	70	new






LED COB CITIZEN


Power	Beam	Flux	CCT	Finish	Code	€	
8W	30°	750 Lm	3000 K	Black	257631	85	new






0,150 Kg/0,0041 m³

Power	Beam	Flux	CCT	Finish	Code	€	_
12W	30°	1000 Lm	3000 K	Black	257655	90	new






	Model	Included	Required	Code	€	_
FILTER HONEYCOMB	Ego 3 W	No	No	260853	3	new
	Ego 8 W	No	No	260860	3	new
	Ego 12 W	No	No	260860	3	new



CRI≥90 3W 30° 230Lm 3000K



m	lx	øm
1	2393	0,49
2	598	0,98
3	266	1,50
4	150	2,00
5	96	2.50

CRI≥90 8W 30° 750Lm 3000K

90° \	m
HIANTH	1
60°	2
XXXX	3
	4
30°	5

CRI≥90 12W 30° 1000Lm 3000K

lx

2877

320

180

115

øm

0,51

1,00

1,50

2,10

2,60



