

Thor new

Adjustable linear projector for surface installation with oblique light effect. Die-cast aluminum body, clear glass diffuser.


Integrated LED source, available in two lengths (500 mm and 1000 mm). Adjustability +/- 90° from the vertical, IP65 protection index, IK06 impact resistance, 3000K color temperature, 24 Vdc power supply input; LED useful life 50.000 h. Optionally available with anti-glare visor.


PRO

High-tech product with high quality materials, intended for professional use.

Source	LED COB	Insulation class	III
Power	8W / 36W	IP	65
Driver included	No	Material	Aluminum
Drivers available	On/Off		
CCT	3000 K		
CRI	≥80		
LED life	50.000 h		


LED SMD OSRAM Driver not included




Power	Beam	Flux	CCT	Finish	Code	€
18 W	30°	1950 Lm	3000 K	Anthracite 	261331	175 <small>new</small>

1,490 Kg/0,0057 m³
Cable lenght 50 cm

LED SMD OSRAM Driver not included





Power	Beam	Flux	CCT	Finish	Code	€
36 W	30°	3900 Lm	3000 K	Anthracite 	261355	275 <small>new</small>

2,460 Kg/0,0108 m³
Cable lenght 50 cm

OPTIONAL Not included



Visor	Power	Finish	Code	€
	18W	Anthracite 	261362	15 <small>new</small>
	36W	Anthracite 	261379	25 <small>new</small>

ON/OFF DRIVER Not included/Required

Power	Output	Measure	Code	€
40 W	24 Vdc	171 x 37 x 61 mm	272108	85 <small>new</small>
100 W	24 Vdc	220 x 68 x 39 mm	226200	130
185 W	24 Vdc	220 x 68 x 39 mm	226217	150

