

Steel

Linear aluminum lamp with direct and indirect light. The indirect light can be turned on or off thanks to the switch positioned on the edge of the fitting. The lamp is available in WIDE model with diffusing downlight optics made of microprismatized PMMA ($UGR < 19$) and in ACCENT model with black reflector ($UGR < 16$). Integrated LED sources, available with CCT 3000 K e 4000 K; CRI ≥ 90 ; lifetime 50.000 h L70B50; IP20. Suitable for offices, business premises and retail.

PRO High-tech product with high quality materials, intended for professional use.


UGR Product with UGR < 16 (Accent), < 19 (Wide).

Source	LED SMD
Driver included	On/Off
Drivers available	No
MacAdam	SDCM 3
Optics	Accent/Wide
CCT	3000 K / 4000 K
CRI	≥ 90
UGR	< 16 (Accent) / < 19 (Wide)
LED life	50.000 h
Insulation class	I
IP	20
Material	Aluminum
Warranty	5 years





Steel




1,990 Kg/0,0178 m³
Cable length 1800 mm

LED SMD SAMSUNG

Up-light included - Driver OSRAM ON/OFF included - UGR <19

Power	Beam	Lumen	CCT	Finish	Code	€
36 W	70°	2600 lm	3000 K	White	267128	255
				Black	270197	255
	2770 lm	4000 K	White	270203	255	
			Black	267135	255	



1,980 Kg/0,0178 m³
Cable length 1800 mm





LED SMD SAMSUNG

Up-light included - Driver OSRAM ON/OFF included - UGR <16

Power	Beam	Lumen	CCT	Finish	Code	€
36 W	60°	2500 lm	3000 K	White	270180	295
				Black	267142	295
	2680 lm	4000 K	White	267159	295	
			Black	270173	295	


UP-LIGHT INFO

Beam	Lumen	CCT
110°	1100 lm	3000 K
	1180 lm	4000 K

	Required	N° Cables	Cables Length	Finish	Code	€
 KIT SUSPENSION	Yes - 1 Kit x power source	1	2000 mm	White	276311	25
				Black	276304	25
 KIT SINGLE CABLE	Yes - 1 Kit x 500 mm	1	2000 mm		271750	11
 KIT SURFACE	Yes - 1 Kit x 1000 mm				270210	28
 KIT CONTINUOS	Yes - 1 Kit x connection				271712	6



Light beam: **BI-EMISSION ACCENT**




m	lx	øm
1	2216	1,20
2	554	2,40
3	246	3,60
4	139	4,80
5	89	6,10



CRI≥90 36W 70° 2770lm 4000K



Light beam: **BI-EMISSION WIDE**



m	lx	øm
1	1173	1,50
2	293	3,10
3	130	4,60
4	73	6,20
5	47	7,70



CRI≥90 36W 60° 2680lm 4000K




Steel Accent



1700

Steel Wide



1700