



Game Round



⌀ 74 mm
0,280 Kg/0,0011 m³

LED COB CREE Driver ON/OFF included - CRI ≥80

Power	Beam	Lumen	CCT	Finish		Code	€
11W	36°	830 lm	2700 K	White	+	285429	41 <i>new</i>
			3000 K	Silver	+	192284	41
		1000 lm	White	+	192291	41	
			Black	+	192277	41	
			Gold	+	192307	41	
			4000 K	White	+	267975	41




⌀ 74 mm
0,280 Kg/0,0011 m³

LED COB CREE Driver ON/OFF included - CRI ≥80

Power	Beam	Lumen	CCT	Finish		Code	€
11W	36°	830 lm	2700 K	Black	+	285412	41 <i>new</i>
			3000 K	Silver	+	192321	41
		1000 lm	White	+	192338	41	
			Black	+	192314	41	
			Gold	+	192345	41	
			4000 K	Black	+	267968	41

DIMMABLE DRIVER* Optional

	Power	Output	Measure (LxHxW)	Code	€
1-10V	12W	250 mA	150 x 43 x 29 mm	217253	35
DALI	11W	250 mA	135 x 20 x 30 mm	202396	50



⌀ 110 mm
0,660 Kg/0,0033 m³

LED COB BRIDGELUX Driver ON/OFF included - CRI ≥90


Power	Beam	Lumen	CCT	Finish		Code	€
20W	24°	2350 lm	3000 K	White	+	273174	80 <i>new</i>
				Black	+	273167	80 <i>new</i>



Light beam: **ACCENT**




Light beam: **SPOT**



m	lx	øm
1	1545	0,69
2	386	1,38
3	171	2,07
4	96	2,77
5	61	3,46



CRI≥90 11W 36° 850lm 3000K



m	lx	øm
1	8645	0,41
2	2161	0,83
3	961	1,20
4	540	1,70
5	346	2,10



CRI≥90 20W 24° 1850lm 3000K

* The dimmable power supplies must be ordered in concomitance with the product and will be included inside the fittings by replacing the on-off power supply.

