


APPLIANCE INLETS WITH FLANGE

- IEC 60309-1/2, EN 60309, VDE 0623
- Protection degree IP44

Appliance Inlet with Flange Quick-Connect TE

- Screwless terminals
- 10° angled
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Protection degree IP44

Amperage	Poles	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	each
		3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h		
16	3	27209	27121	27210				10	140
16	4	27211	27207	27122				10	215
16	5	27215	27216	27124				10	240
32	3	27218	27219	27220				10	275
32	4	27221	27222	27223				10	250
32	5	27247	27248	27249				10	315



Ampere Poles	16 3	16 4	16 5	32 3	32 4	32 5
a	85.0	85.0	85.0	85.0	85.0	85.0
b	85.0	85.0	85.0	85.0	85.0	85.0
c	70.0	70.0	70.0	70.0	70.0	70.0
d	70.0	70.0	70.0	70.0	70.0	70.0
e ø	6.3	6.3	6.3	6.3	6.3	6.3
f	11.0	11.0	11.0	11.0	11.0	11.0
h	104.0	110.0	116.0	121.0	121.0	127.0
i	83.0	90.0	92.0	96.0	96.0	100.0
Cond. mm² min	1	1	1	2.5	2.5	2.5
Cond. mm² max	2.5	2.5	2.5	6	6	6


Fig.: Type 27124

5 MB 21

Appliance Inlet with Flange TE

- Screw terminals
- 10° angled
- Box terminals
- High-temperature-resistant contact carrier
- Nickel plated contacts
- Protection degree IP44

Amperage	Poles	110V 50-60 Hz	230V 50-60 Hz	400V 50-60 Hz	500V 50-60 Hz	100-300Hz > 50V	301-500Hz > 50V	Qty	each
		3pol 4pol 5pol 4h 4h 4h	3pol 4pol 5pol 6h 9h 9h	3pol 4pol 5pol 9h 6h 6h	3pol 4pol 5pol 7h 7h 7h	3pol 4pol 5pol 10h 10h 10h	3pol 4pol 5pol 2h 2h 2h		
63	3	2770	2771	2772				5	550
63	4	2773	2774	2775				5	570
63	5	2779	2780	2781				5	625



Ampere Poles	63 3	63 4	63 5
a	107.0	107.0	107.0
b	100.0	100.0	100.0
c	85.0	85.0	85.0
d	77.0	77.0	77.0
e ø	6.5	6.5	6.5
f	12.0	12.0	12.0
h	155.0	155.0	155.0
i	118.0	118.0	118.0
Cond. mm² min	6	6	6
Cond. mm² max	16	16	16

Fig.: Type 2781

5 MB 21