

Ego ^{new}

Linear system composed of extruded aluminum profile and lighting elements with magnetic fixing and mechanical safety lock. The system is available in black, white or satin brass color for ceiling, suspended or recessed installation. The profile section is 26 mm wide and 27 mm or 52 mm high. Available in two lengths: 1000 mm and 2000 mm. Possibility of assembly with different source modules which can be combined following the desired disposition and can be modified when needed: TRACK SINGLE or DOUBLE modules for a spot illumination, ACCENT module with glare control (UGR < 19), PENDANT TUBE module for a localized illumination and WIDE and WALL WASHER modules for a diffused and uniform illumination. Integrated LED with color temperature of 3000k and CRI 90; IP20 protection, insulation class III, 48 Vdc power source,; LED useful life 50.000 h L70B5. The system is also available with DALI dimmable version. Ideal for lighting small and in large environments where great flexibility and color rendering is required, such as MUSEUMS, COMMERCIAL, RESIDENTIAL and RETAIL spaces.


PRO High-tech product with high quality materials, intended for professional use.

UGR Product with UGR <19 (Accent, Pendant).

Source	LED COB / SMD
Driver included	No
Drivers available	On/Off
Control	On/Off / DALI
MacAdam	SDCM 3
CCT	3000K
CRI	≥90
UGR	<19 (Accent, Pendant)
LED life	50.000h
Insulation class	III
IP	20
Material	Aluminum
Warranty	5 years




Ego Pendant and Wall Washer



0,540 Kg/0,0038 m³

LED COB CITIZEN UGR <19


Power	Beam	Lumen	CCT	Control	Finish	Code	€
12 W	30°	1000 lm	3000 K	On-Off	White	282879	145 <i>new</i>
					Black	257747	145
				DALI	White	286327	185 <i>new</i>
					Black	286310	185 <i>new</i>



0,320 Kg/0,0026 m³

LED SMD SAMSUNG

Power	Beam	Lumen	CCT	Control	Finish	Code	€
7 W	-	650 lm	3000 K	On-Off	White	283005	90 <i>new</i>
					Black	257815	90
				DALI	White	286464	140 <i>new</i>
					Black	286457	140 <i>new</i>



0,560 Kg/0,0012 m³

LED SMD SAMSUNG


Power	Beam	Lumen	CCT	Control	Finish	Code	€
13 W	-	1300 lm	3000 K	On-Off	White	283012	120 <i>new</i>
					Black	257822	120
				DALI	White	286488	165 <i>new</i>
					Black	286471	165 <i>new</i>



Light beam: ACCENT




Light beam: ASYMMETRICAL



m	lx	øm
1	2877	0,51
2	719	1,00
3	320	1,50
4	180	2,10
5	115	2,60



CRI≥90 12W 30° 1000lm 3000K



CRI≥90 13W 1300lm 3000K

