


proiectoare cu LED si cu senzor de miscare - IP65



- Proiector cu LED si senzor
- Material din aluminiu
- Tip LED: SMD

unghi detectie: 140°
distanța detectie max.: 10m
reglaj timp: 20sec. ... 3min.



IP65/IP44C E


COD dablerom	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)	
					L (mm)	W (mm)	h (mm)		
3-301011	antracit	10W	alba	4100k	1100	164	118	45	1/16
3-302001	alb	20W	alba	4100k	1700	150	166	52	1/16
3-302011	antracit	20W	alba	4100k	2200	164	118	48	1/16
3-303001	alb	30W	alba	4100k	3300	194	148	48	1/8
3-303011	antracit	30W	alba	4100k	3300	194	148	48	1/8
3-305001	alb	50W	alba	4100k	4500	240	220	52	1/10
3-305011	antracit	50W	alba	4100k	5500	224	178	48	1/8

proiectoare cu LED si cu fotocelula - IP65



- Proiector cu LED si fotocelula
- Material din aluminiu
- Tip LED: SMD

activare la <5 lux



IP65C E

COD	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)	
					L (mm)	W (mm)	h (mm)		
3-030101	alb	10W	alba	4000k	1050	125	110	50	1/30
3-0301011	negru	10W	alba	4000k	1050	125	110	50	1/30
3-030201	alb	20W	alba	4000k	1800	150	120	50	1/20
3-0302011	negru	20W	alba	4000k	1800	150	120	50	1/20
3-030301	alb	30W	alba	4000k	2800	185	145	50	1/12
3-0303011	negru	30W	alba	4000k	2800	185	145	50	1/12
3-030501	alb	50W	alba	4000k	4800	210	175	50	1/6
3-0305011	negru	50W	alba	4000k	4800	210	175	50	1/6
3-0307011	negru	70W	alba	4000k	7000	295	245	55	1/4
3-03010011	negru	100W	alba	4000k	9500	335	290	55	1/4