

corpuri de iluminat (tip T5) interconectabile cu LED



5W - 10W - 15W - 20W



25000 ore
de funcționare

- Corp "LED" cu montaj aparent
- Material din aluminiu
- Cu intrerupator si Interconectabile
- Cu cablu de 15cm
- Include clips de fixare pe perete
- Include banda dubla adeziva



230V

-25°C +35°C

Ra>80

Pf>0,5



IP20



COD	CULOARE	PUTERE (W)	BUC. max. interconect.	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)	
						L (mm)	W (mm)	h (mm)		
3-905601	alb	5W	30	alba	4000k	525	300	22	34	6/48
3-90560	alb	5W	30	rece	6400k	525	300	22	34	6/48
3-910600	alb	10W	15	calda	3000k	1050	600	22	34	6/48
3-910601	alb	10W	15	alba	4000k	1050	600	22	34	6/48
3-91060	alb	10W	15	rece	6400k	1050	600	22	34	6/48
3-915601	alb	15W	9	alba	4000k	1550	900	22	34	6/48
3-91560	alb	15W	9	rece	6400k	1550	900	22	34	6/48
3-920601	alb	20W	7	alba	4000k	2150	1200	22	34	6/48
3-92060	alb	20W	7	rece	6400k	2150	1200	22	34	6/48

corpuri de iluminat cu intrerupator si LED - IP40



9W - 18W - 24W - 36W - 50W



25000 ore
de funcționare

- Corp "LED" cu montaj aparent
- Material din policarbonat (PC)
- Cu intrerupator



230V

-25°C +35°C

Ra>80

Pf>0,5



IP40



COD	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)	
					L (mm)	W (mm)	h (mm)		
3-9940100	alb	9W	calda	3000k	900	300	57	26	1/25
3-994011	alb	9W	alba	4000k	900	300	57	26	1/25
3-994010	alb	9W	rece	6000k	900	300	57	26	1/25
3-91840100	alb	18W	calda	3000k	1850	600	57	26	1/25
3-9184011	alb	18W	alba	4000k	1850	600	57	26	1/25
3-9184010	alb	18W	rece	6000k	1850	600	57	26	1/25
3-92440100	alb	24W	calda	3000k	2500	900	57	26	1/25
3-9244011	alb	24W	alba	4000k	2500	900	57	26	1/25
3-9244010	alb	24W	rece	6000k	2500	900	57	26	1/25
3-93640100	alb	36W	calda	3000k	3850	1200	57	26	1/25
3-9364011	alb	36W	alba	4000k	3850	1200	57	26	1/25
3-9364010	alb	36W	rece	6000k	3850	1200	57	26	1/25
3-95040100	alb	50W	calda	3000k	5450	1500	57	26	1/25
3-9504011	alb	50W	alba	4000k	5450	1500	57	26	1/25
3-9504010	alb	50W	rece	6000k	5450	1500	57	26	1/25