



corpuri de iluminat PT cu LED - IP65



- Corp de iluminat cu montaj aparent
- Material : Policarbonat
- Lumina intr-un singur sens
- Putere maxima : 2W
- Sistem de pornire inclus



dreptunghiular 2W




COD	TENSIVUNE (V)	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)
						L (mm)	W (mm)	h (mm)	
3-9780	230V	alb	2W	calda 3000k	100	100	60	33	1/60
3-9781	230V	grafit	2W	calda 3000k	100	100	60	33	1/60
3-9786	230V	gri	2W	calda 3000k	100	100	60	33	1/60



- Corp de iluminat cu montaj aparent
- Material : Policarbonat
- Lumina intr-un singur sens
- Putere maxima : 3W
- Sistem de pornire inclus



dreptunghiular 3W




COD	TENSIVUNE (V)	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)
						L (mm)	W (mm)	h (mm)	
3-9770	230V	alb	3W	calda 3000k	200	160	70	33	1/20
3-9771	230V	grafit	3W	calda 3000k	200	160	70	33	1/20
3-9776	230V	gri	3W	calda 3000k	200	160	70	33	1/20



- Corp de iluminat cu montaj aparent
- Material : Policarbonat
- Lumina intr-un singur sens
- Putere maxima : 4W
- Sistem de pornire inclus



dreptunghiular 4W



COD	TENSIVUNE (V)	CULOARE	PUTERE (W)	LUMINA	LUMEN (lm)	DIMENSIUNI			PACK. (buc)
						L (mm)	W (mm)	h (mm)	
3-9760	230V	alb	4W	calda 3000k	250	220	80	36	1/24
3-9761	230V	grafit	4W	calda 3000k	250	220	80	36	1/24
3-9766	230V	gri	4W	calda 3000k	250	220	80	36	1/24