

benzi cu led - 24V IP20



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



montaj pe profil de aluminiu



7.2W/m - 24V - SMD:2835

Prelungire max.: 10m

lumina ≈ 720lm/m



IP20 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-34247000	24V DC	7.2W/m	calda-2700k	60	2835	8	2	100	5/50
30-3424700	24V DC	7.2W/m	calda	60	2835	8	2	100	5/50
30-342471	24V DC	7.2W/m	alba	60	2835	8	2	100	5/50
30-342470	24V DC	7.2W/m	rece	60	2835	8	2	100	5/50
30-3424799	24V DC	7.2W/m	RGB	30	5050	10	2	165	5/50



14.4W/m - 24V - SMD:2835

Prelungire max.: 10m

lumina ≈ 1440lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-3402414000	24V DC	14.4W/m	calda-2700k	140	2835	10	2	50	5/50
05-34249/calda	24V DC	14.4W/m	calda	140	2835	10	2	50	5/50
05-34249/alb	24V DC	14.4W/m	alba	140	2835	10	2	50	5/50
05-34249/rece	24V DC	14.4W/m	rece	140	2835	10	2	50	5/50
05-34249/RGB	24V DC	14.4W/m	RGB	60	5050	10	2	100	5/50
05-34249/RGBW	24V DC	14.4W/m	RGB+alb	60	5050	10	2	170	5/50



24W/m - 24V - SMD:2835

Prelungire max.: 10m

lumina ≈ 2400lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-340242400	24V DC	14.4W/m	calda	252	2835	10	2	28	5/50
30-34024241	24V DC	14.4W/m	alba	252	2835	10	2	28	5/50
30-34024240	24V DC	14.4W/m	rece	252	2835	10	2	28	5/50
30-340242499	24V DC	14.4W/m	RGB+alb	144	5050	12	2	83	5/50



ECO



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



montaj pe profil de aluminiu



14.4W/m - 24V - SMD:5050

Prelungire max.: 10m

lumina ≈ 1100lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-44249/calda	24V DC	14.4W/m	calda	60	5050	10	2	100	5/50

- * verificati temperatura de culoare inainte de montare
- * nu indoiti banda la unghi drept de 90°

