

benzi cu led - 230V IP65



**Include
cablu de alimentare
si capac**



- Benzi LED SMD
- Unghi de lumina la 120°




la rola de 10m

10W/m - 230V - SMD:2835

Prelungire max.: 40m

lumina ≈ 800lm/m



IP65 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI W (mm)	DIMENSIUNI h (mm)	TAIERE min. (mm)	PACK. (metri)
30-36100	230V	10W/m	calda	60	2835	15	8	1000	10/110
30-36101	230V	10W/m	alba	60	2835	15	8	1000	10/110
30-3610	230V	10W/m	rece	60	2835	15	8	1000	10/110

la rola de 40m


COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI W (mm)	DIMENSIUNI h (mm)	TAIERE min. (mm)	PACK. (metri)
30-360100	230V	10W/m	calda	60	2835	14	8	1000	40
30-360101	230V	10W/m	alba	60	2835	14	8	1000	40
30-36010	230V	10W/m	rece	60	2835	14	8	1000	40

la rola de 10m

15W/m - 230V - SMD:2835

Prelungire max.: 25m

lumina ≈ 1.200lm/m



IP65 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI W (mm)	DIMENSIUNI h (mm)	TAIERE min. (mm)	PACK. (metri)
30-361500	230V	15W/m	calda	120	2835	15	8	1000	10/110
30-36151	230V	15W/m	alba	120	2835	15	8	1000	10/110
30-36150	230V	15W/m	rece	120	2835	15	8	1000	10/110

la rola de 25m

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	LED (tip)	DIMENSIUNI W (mm)	DIMENSIUNI h (mm)	TAIERE min. (mm)	PACK. (metri)
30-3601500	230V	15W/m	calda	120	2835	15	8	1000	25
30-360151	230V	15W/m	alba	120	2835	15	8	1000	25
30-360150	230V	15W/m	rece	120	2835	15	8	1000	25

* verificati temperatura de culoare inainte de montare

* nu indoiti banda la unghi drept de 90°



accesorii pentru benzi cu led 230V IP65

COD	DENUMIRE	PACK. (buc)
30-360	cablu de alimentare 230V	1/50



COD	DENUMIRE	PACK. (buc)
30-3601	conector ptr. banda 10W & 15W	10/100
30-3602	capac ptr. banda 10W & 15W	10/200



30-3601



30-3602

COD	DENUMIRE	PACK. (buc)
30-3603	sistem de prindere ptr. banda 10W	10/200



30-3603