

benzi cu led - 230V IP65



- Benzi LED SMD
- Unghi de lumina la 120°



**Rola la 10metri
si include
cablu de alimentare
si capac**

10W/m - 230V - SMD:2835

Prelungire max.: 40m

lumina ≈ 1.000lm/m



IP65 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-36100	230V	10W/m	calda	60	2835	14	8	1000	10/100
30-36101	230V	10W/m	alba	60	2835	14	8	1000	10/100
30-3610	230V	10W/m	rece	60	2835	14	8	1000	10/100

15W/m - 230V - SMD:2835

Prelungire max.: 25m

lumina ≈ 1.500lm/m



IP65 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm)	h (mm)	TAIERE min. (mm)	PACK. (metri)
30-361500	230V	15W/m	calda	120	2835	15	8	1000	10/100
30-36151	230V	15W/m	alba	120	2835	15	8	1000	10/100
30-36150	230V	15W/m	rece	120	2835	15	8	1000	10/100

* verificati temperatura de culoare inainte de montare

* nu indoiti banda la unghi drept de 90°



accesorii pentru benzi cu led 230V IP65

COD	DENUMIRE	PACK. (buc)
30-360	cablu de alimentare 230V	1/50



COD	DENUMIRE	PACK. (buc)
30-3601	conector ptr. banda 10W & 15W	10/100
30-3602	capac ptr. banda 10W & 15W	10/200



30-3601

30-3602

COD	DENUMIRE	PACK. (buc)
30-3603	sistem de prindere ptr. banda 10W	10/200
30-3606	sistem de prindere ptr. banda 15W	10/200



30-3603

30-3606