

benzi cu led "ECO" - IP54



ECO



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



cu profil de aluminiu



4.8W/m - 12V - SMD:3528

Prelungire max.: 5m

lumina ≈ 380lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-441211/cald	12V DC	4.8W/m	calda	60 3528	8 3	50	5/50
30-441211/alb	12V DC	4.8W/m	alba	60 3528	8 3	50	5/50
30-441211/rece	12V DC	4.8W/m	rece	60 3528	8 3	50	5/50



7.2W/m - 12V - SMD:5050

Prelungire max.: 5m

lumina ≈ 550lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-441221/cald	12V DC	7.2W/m	calda	30 5050	10 3	100	5/50
30-441221/alb	12V DC	7.2W/m	alba	30 5050	10 3	100	5/50
30-441221/rece	12V DC	7.2W/m	rece	30 5050	10 3	100	5/50
30-441221/RGB	12V DC	7.2W/m	RGB	30 5050	10 3	100	5/50



14.4W/m - 12V - SMD:5050

Prelungire max.: 5m

lumina ≈ 1100lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-441291/cald	12V DC	14.4W/m	calda	60 5050	10 3	50	5/50
30-441291/alb	12V DC	14.4W/m	alba	60 5050	10 3	50	5/50
30-441291/rece	12V DC	14.4W/m	rece	60 5050	10 3	50	5/50



14.4W/m - 24V - SMD:5050

Prelungire max.: 5m

lumina ≈ 1100lm/m



IP54 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-442419/cald	24V DC	14.4W/m	calda	60 5050	10 3	100	5/50
30-442419/alb	24V DC	14.4W/m	alba	60 5050	10 3	100	5/50
30-442419/rece	24V DC	14.4W/m	rece	60 5050	10 3	100	5/50
30-442419/RGB	24V DC	14.4W/m	RGB	60 5050	10 3	100	5/50

- * verificati temperatura de culoare inainte de montare
- * nu indoiti banda la unghi drept de 90°

