

## benzi cu led "ECO" - IP20



# ECO



- Benzi LED SMD
- Cu autocolant
- Unghi de lumina la 120°



cu profil de aluminiu



4.8W/m - 12V - SMD:3014

Prelungire max.: 5m

lumina ≈ 380lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-44112/cald	12V DC	4.8W/m	calda	60 3014	8 2	50	5/50
30-44112/alb	12V DC	4.8W/m	alba	60 3014	8 2	50	5/50
30-44112/rece	12V DC	4.8W/m	rece	60 3014	8 2	50	5/50



7.2W/m - 12V - SMD:5050

Prelungire max.: 5m

lumina ≈ 550lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-44122/cald	12V DC	7.2W/m	calda	30 5050	10 2	100	5/50
30-44122/alb	12V DC	7.2W/m	alba	30 5050	10 2	100	5/50
30-44122/rece	12V DC	7.2W/m	rece	30 5050	10 2	100	5/50
30-44122/RGB	12V DC	7.2W/m	RGB	30 5050	10 2	100	5/50



14.4W/m - 12V - SMD:5050

Prelungire max.: 5m

lumina ≈ 1100lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-44129/cald	12V DC	14.4W/m	calda	60 5050	10 2	50	5/50
30-44129/alb	12V DC	14.4W/m	alba	60 5050	10 2	50	5/50
30-44129/rece	12V DC	14.4W/m	rece	60 5050	10 2	50	5/50
30-44129/RGB	12V DC	14.4W/m	RGB	60 5050	10 2	50	5/50



14.4W/m - 24V - SMD:5050

Prelungire max.: 5m

lumina ≈ 1100lm/m



IP20 CE

COD dablerom	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m) (tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-44249/cald	24V DC	14.4W/m	calda	60 5050	10 2	100	5/50
30-44249/alb	24V DC	14.4W/m	alba	60 5050	10 2	100	5/50
30-44249/rece	24V DC	14.4W/m	rece	60 5050	10 2	100	5/50
30-44249/RGB	24V DC	14.4W/m	RGB	60 5050	10 2	100	5/50

- \* verificati temperatura de culoare inainte de montare
- \* nu indoiti banda la unghi drept de 90°

