

benzi cu COB led - SUPER DENSE - IP20


COB led
SUPER DENSE


- Benzi LED COB
- Cu autocolant
- Unghi de lumina la 120°


montaj pe profil de aluminiu

8W/m - 24V - COB LED
Prelungire max.: 10m

lumina ≈ 880lm/m


IP20 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-47800	24V DC	8W/m	calda	320	COB	8 2	50	5/50
30-4781	24V DC	8W/m	alba	320	COB	8 2	50	5/50
30-4780	24V DC	8W/m	rece	320	COB	8 2	50	5/50


11W/m - 24V - COB LED
Prelungire max.: 10m

lumina ≈ 1.210lm/m


IP20 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-471100	24V DC	11W/m	calda	480	COB	8 2	50	5/50
30-47111	24V DC	11W/m	alba	480	COB	8 2	50	5/50
30-47110	24V DC	11W/m	rece	480	COB	8 2	50	5/50


14W/m - 24V - COB LED
Prelungire max.: 10m

lumina ≈ 1.540lm/m


IP20 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-471400	24V DC	14W/m	calda	480	COB	8 2	50	5/50
30-47141	24V DC	14W/m	alba	480	COB	8 2	50	5/50
30-47140	24V DC	14W/m	rece	480	COB	8 2	50	5/50
30-471409	24V DC	14W/m	RGB	576	COB	8 2	26	5/50


18W/m - 24V - COB LED
Prelungire max.: 10m

lumina ≈ 1.980lm/m


IP20 CE

COD	TENSIUNE (V)	PUTERE (W/m)	LUMINA	LED (nr./m)	(tip)	DIMENSIUNI W (mm) h (mm)	TAIERE min. (mm)	PACK. (metri)
30-471800	24V DC	18W/m	calda	528	COB	10 2	45	5/50
30-47181	24V DC	18W/m	alba	528	COB	10 2	45	5/50
30-47180	24V DC	18W/m	rece	528	COB	10 2	45	5/50
30-471610	24V DC	16W/m	RGB+W	748	COB	10 2	62	5/50



- * verificati temperatura de culoare inainte de montare
- * nu indoiti banda la unghi drept de 90°

