

CONNECTORS

OPTIMA Series



| Poles | Volt | Hz. | h. | 16A | | 16A | |
|--------|---------|-------|----|----------|-------|-----------|-------|
| 2P+E | 100-130 | 50/60 | 4 | 313.1640 | 10/50 | 313.1640P | 10/50 |
| 2P+E | 200-250 | 50/60 | 6 | 313.1643 | 10/50 | 313.1643P | 10/50 |
| 3P+E | 380-415 | 50/60 | 6 | 313.1646 | 10/50 | 313.1646P | 10/50 |
| 3P+N+E | 346-415 | 50/60 | 6 | 313.1647 | 10/50 | 313.1647P | 10/50 |

| Poles | Volt | Hz. | h. | 32A | | 32A | |
|--------|---------|-------|----|----------|-------|-----------|-------|
| 2P+E | 100-130 | 50/60 | 4 | 313.3240 | 10/40 | 313.3240F | 10/40 |
| 2P+E | 200-250 | 50/60 | 6 | 313.3243 | 10/40 | 313.3243F | 10/40 |
| 3P+E | 380-415 | 50/60 | 6 | 313.3246 | 10/40 | 313.3246F | 10/40 |
| 3P+N+E | 346-415 | 50/60 | 6 | 313.3247 | 10/40 | 313.3247F | 10/40 |



| Pole | Volt | Hz. | h. | 63A | |
|--------|---------|-------|----|----------|------|
| 2P+T | 200-250 | 50/60 | 6 | 313.6343 | 6/24 |
| 3P+T | 380-415 | 50/60 | 6 | 313.6346 | 6/24 |
| 3P+N+T | 346-415 | 50/60 | 6 | 313.6347 | 6/24 |

TERMINALS



FAST WIRING - Anti vibrations



FAST WIRING



Optimal connections for high currents.

CONNECTORS

XENIA Series



| Poles | Volt | Hz. | h. | 16A | |
|--------|---------|-------|----|----------|-------|
| 2P+E | 100-130 | 50/60 | 4 | 314.1640 | 10/50 |
| 2P+E | 200-250 | 50/60 | 6 | 314.1643 | 10/50 |
| 3P+E | 380-415 | 50/60 | 6 | 314.1646 | 10/50 |
| 3P+N+E | 346-415 | 50/60 | 6 | 314.1647 | 10/50 |

| Poles | Volt | Hz. | h. | 32A | |
|--------|---------|-------|----|----------|-------|
| 2P+E | 100-130 | 50/60 | 4 | 314.3240 | 10/40 |
| 2P+E | 200-250 | 50/60 | 6 | 314.3243 | 10/40 |
| 3P+E | 380-415 | 50/60 | 6 | 314.3246 | 10/40 |
| 3P+N+E | 346-415 | 50/60 | 6 | 314.3247 | 10/40 |

DOMESTIC STANDARD PLUG AND SOCKETS

The range of splashproof products for uses in the domestic and tertiary sectors is completed by the **QUICK** Series mobile plug and sockets. Inconspicuous, thanks to their black colour that makes them go unnoticed, they are also practically indestructible thanks to the sturdy rubber housing with excellent grip, whilst the IP44 protection rating makes them suitable for use in dusty and humid environments.

PLUG

QUICK Series



RUBBER HOUSING

| Standard | Description | | |
|---------------|-------------|----------|--------|
| French-German | 16A 2P+E | 110.3100 | 10/150 |

CONNECTORS

QUICK Series



RUBBER HOUSING

| Standard | Description | | |
|----------|-------------|----------|--------|
| German | 16A 2P+E | 110.3150 | 10/150 |
| French | 16A 2P+E | 110.3160 | 10/150 |