

CONNECTORS

OPTIMA Series



Poles	Volt	Hz.	h.	16A		16A	
2P+E	100-130	50/60	4	318.1640	10/50	318.1640P	10/50
2P+E	200-250	50/60	6	318.1643	10/50	318.1643P	10/50
3P+E	380-415	50/60	6	318.1646	10/50	318.1646P	10/50
3P+N+E	346-415	50/60	6	318.1647	10/50	318.1647P	10/50

Poles	Volt	Hz.	h.	32A		32A	
2P+E	100-130	50/60	4	318.3240	10/40	318.3240F	10/40
2P+E	200-250	50/60	6	318.3243	10/40	318.3243F	10/40
3P+E	380-415	50/60	6	318.3246	10/40	318.3246F	10/40
3P+N+E	346-415	50/60	6	318.3247	10/40	318.3247F	10/40



Poles	Volt	Hz.	h.	63A	
2P+E	200-250	50/60	6	318.6343	6/24
3P+E	380-415	50/60	6	318.6346	6/24
3P+N+E	346-415	50/60	6	318.6347	6/24

Poles	Volt	Hz.	h.	125A	
3P+E	380-415	50/60	6	318.12546	1/8
3P+N+E	346-415	50/60	6	318.12547	1/8

TERMINALS



SCREW TERMINALS



SPRING TERMINALS

FAST WIRING - Anti vibrations



INSULATION PERFORATING TERMINALS

FAST WIRING



MANTLE TERMINALS

Optimal connections for high currents.