

# IR Quattro HD

**Fits on the ceiling.**

**And sees what others dream of.**

HD isn't just restricted to televisions but from now on also used in presence detectors. Because IR Quattro HD provides extremely high-definition detection. 4,800 switching zones and a square detection footprint with a presence zone covering a true 64 m<sup>2</sup> leave no margin whatsoever for inadvertent triggering and blind spots. Unique: the presence zone can be mechanically scaled without the slightest loss of quality. This means IR Quattro HD applications can be planned and configured with absolute precision in medium to large-size offices, conference and meeting rooms, class rooms and lecture theatres as well as sports halls and warehouses. Something others can only dream of.

CONTROL  
**PRO**  
SYSTEM



Infrared sensor  
360°



max. 8m x 8m  
presence

**HD**

4800 zones

**2000w**

max.

**DIM**

1-10 V



2 channels



LiveLink



2,5-10m

**iQ**

iQ-mode




energy  
saving

**5 JAHRE**  
GARANTIE

manufacturer's  
warranty




EAN IR Quattro HD, COM1	4007841 002794
EAN IR Quattro HD, COM1, surface-mounted	4007841 592400
EAN IR Quattro HD, COM2	4007841 002770
EAN IR Quattro HD, DALI	4007841 002756
EAN IR Quattro HD, DALI-2	4007841 057497
EAN IR Quattro HD, DALI plus	4007841 035204
EAN IR Quattro HD, DALI plus, surface-mounted	4007841 035273
EAN IR Quattro HD, DIM	4007841 002787
EAN IR Quattro HD, KNX	4007841 058470
EAN IR Quattro HD, LiveLink	4007841 009717



**You will find information on the interfaces as well as wiring diagrams from page 142 onwards.**

Type	Presence detector
Dimensions (H x W x D)	120 x 120 x 76 mm
Dimensions (H x W x D), surface-mounted	120 x 120 x 65 mm
Sensor type	Passive infrared
Where to use	Indoors
Installation	Ceiling
Mounting height	2.5 - 10 m
Recommended mounting height	2.8 m
Square presence detection zone	max. 8 x 8 m (64 m <sup>2</sup> )
Square detection zone, radial	max. 8 x 8 m (64 m <sup>2</sup> )
Square detection zone, tangential	max. 20 x 20 m (400 m <sup>2</sup> )
Reach mechanically adjustable	Yes
Sensor system	13 detection levels, 4800 switching zones
Parallel-connected configurations	Master/master, master/slave
User-friendly setting	Teach-In (with optional remote control RC8)
Twilight setting	10 - 1000 lx, ∞/daylight
Twilight setting DIM	100 - 1000 lx, ∞/daylight
IP rating	IP20
IP rating with AP Box (from accessories)	IP54
Temperature range	-25 to +55°C
Enclosure	UV-resistant, paintable



IR Quattro HD detection zone  
Possible mounting height: 2.5 - 10 m  
Orange: presence and radial  
Black: tangential

**Wiring diagrams from page 142**

**Optional accessories**

EAN User remote control RC5	4007841 592806
EAN Service remote control RC8	4007841 559410
EAN Remote control Smart Remote	4007841 009151
EAN surf-mount. adapter, Control PRO, surf-mount. Box	4007841 000363
EAN guard cage	4007841 003036
EAN Ceiling box Ø68 mm	4007841 052812

Refer to the 'Accessories' section for further information.



Surface-mounted version (AP)

4 pyros with DSP  
(Digital Signal Processing)



Optional remote controls refer to page 300



For optional surface-mounted adapter (IP54, KNX), refer to page 300



Optional guard cage refer to page 300

