

SET TUBURI TERMOCONTRACTABILE



**Ray
Tech**



- Set cu tuburi termocontractabile - pretaiate
- Raport de contractie : 2:1
- Gata de utilizare si sortate dupa dimensiuni
- Setul contine toate dimensiunile
- Doua variante: pe negru si diverse culori
- Rezistenta dupa imbatranire: 14.5 MPa
- Timp scazut de lucru
- Flexibil
- Temperatura de contractie: +125°C

COD	DENUMIRE	CONTRACTIE Ø D / d (mm)	LUNGIME (mm)	CULOARE	BUC./SET	PACK. (set)
44-THERMOMIN-N	THERMO MINIMIX-N	1.0 / 0.5	97	negru	60	1
		2.0 / 1.0	97	negru	40	
		3.0 / 1.5	97	negru	30	
		4.5 / 2.25	97	negru	20	
		6.0 / 3.0	97	negru	10	
		9.0 / 4.5	97	negru	10	
44-THERMOMIN-MC	THERMO MINIMIX-MC	1.0 / 0.5	97	trans.10, alb10, albastru10 rosu10, galben10, negru10	60	1
		2.0 / 1.0	97	trans.7, alb7, albastru6 rosu7, galben7, negru6	40	
		3.0 / 1.5	97	trans.5, alb5, albastru5 rosu5, galben5, negru5	30	
		4.5 / 2.25	97	trans.4, alb4, albastru4 rosu4, galben4	20	
		6.0 / 3.0	97	trans.2, alb2, albastru2 rosu2, galben2	10	
		9.0 / 4.5	97	trans.2, alb2, albastru2 rosu2, galben2	10	

TUB TERMOCONTRACTABIL -Rola - Ray Roll



**Ray
Tech**



- Ambalaj tip dispenser
- Raport de contractie : 2:1
- Rezistenta la rupere: 14.8 MPa
- Intindere: 460%
- Rezistenta dupa imbatranire: 14.5 MPa
- Intindere dupa imbatranire: 480%
- Rezistenta dielectrica: 17KV/mm
- Rezistenta la foc: VW1
- Temperatura de contractie: +125°C

COD	DENUMIRE	CONTRACTIE Ø D / d (mm)	GROSIME S (mm)	CULOARE	LUNGIME (m)	PACK. (rola)
44-RAYROLL-1.6	RAYROLL 1.6 negru-20m	1.6 / 0.8	0.5	negru	20	1
44-RAYROLL-2.4	RAYROLL 2.4 negru-20m	2.4 / 1.2	0.55	negru	20	1
44-RAYROLL-3.2	RAYROLL 3.2 negru-10m	3.2 / 1.6	0.55	negru	10	1
44-RAYROLL-4.8	RAYROLL 4.8 negru-10m	4.8 / 2.4	0.55	negru	10	1
44-RAYROLL-6.4	RAYROLL 6.4 negru-10m	6.4 / 3.2	0.65	negru	10	1
44-RAYROLL-9.5	RAYROLL 9.5 negru-10m	9.5 / 4.8	0.65	negru	10	1
44-RAYROLL-12.7	RAYROLL 12.7 negru-10m	12.7 / 6.4	0.65	negru	10	1
44-RAYROLL-19.0	RAYROLL 19.0 negru-5m	19.0 / 9.5	0.8	negru	5	1
44-RAYROLL-25.4	RAYROLL 25.4 negru-5m	25.4 / 12.7	0.95	negru	5	1