

■ Enclosed change-over switch disconnectors >> Surface mounting - Thermoplastic version

ISOLATORS Series

590.



For general use [I-O-II]

ENCLOSED CHANGE OVER SWITCH

IP55

IP65

GENERAL

Current	Poles	Switch size	Dimension				
16A	3P	C1	155x210x107mm		590.GE1603-C ^{[5][6]} 1/5		
	3P+N				590.GE1605-C ^{[5][4][6]} 1/5		
25A	3P				590.GE2503-C ^{[5][6]} 1/5		
	3P+N				590.GE2505-C ^{[5][4][6]} 1/5		
32A	3P				590.GE3203-C ^{[5][6]} 1/5		
	3P+N				590.GE3205-C ^{[5][4][6]} 1/5		
40A	3P				590.GE4003-C ^{[5][6]} 1/5		
	3P+N				590.GE4005-C ^{[5][4][6]} 1/5		
63A	3P			C2	228x308x128mm		590.GE6303-C ^{[1][2][3]} 1
	3P+N						590.GE6305-C ^{[1][2][4][3]} 1
80A	3P						590.GE8003-C ^{[1][2][3]} 1
	3P+N						590.GE8005-C ^{[1][2][4][3]} 1
100A	3P		590.GE10003-C ^{[1][2][3]} 1				
	3P+N		590.GE10005-C ^{[1][2][4][3]} 1				
125A	3P	C3	308x388x128mm				590.GE12503-C ^{[1][2][3]} 1
	3P+N						590.GE12505-C ^{[1][2][4][3]} 1
160A	3P						590.GE16003-C ^{[1][2][3]} 1
	3P+N						590.GE16005-C ^{[1][2][4][3]} 1

- ¹ Handle padlockable in OFF only (3 padlocks)
- ² Equipped with door interlock
- ³ Blank sides
- ⁴ With late break and early make neutral pole
- ⁵ Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
- ⁶ Break-through cable entries

1.5

