

■ Enclosed switch disconnectors >> Surface mounting - Thermoplastic version [16A÷40A] GE

ISOLATORS Series

590.



For general use [SPECIAL]

For general use

SWITCH DISCONNECTOR

IP65

GENERAL

Current	Poles	Switch size	Dimension	[SPECIAL]		[GENERAL]			
16A	6P	Y3	155x210x107mm	<b>590.EL1606</b>	1/5	<b>590.GE1606</b>	1/5		
	8P			<b>590.EL1608</b> <sup>1</sup>	1/5	<b>590.GE1608</b> <sup>1</sup>	1/5		
20A	2P	Y1	105x150x82mm	<b>590.EL2012</b>	1/12	<b>590.GE2012</b>	1/12		
	3P			<b>590.EL2013</b>	1/12	<b>590.GE2013</b>	1/12		
	4P			<b>590.EL2015</b> <sup>1</sup>	1/12	<b>590.GE2014</b>	1/12		
	3P+N			<b>590.EL2015</b> <sup>1</sup>	1/12	<b>590.GE2015</b> <sup>1</sup>	1/12		
25A	6P	Y3	155x210x107mm	<b>590.EL2506</b>	1/5	<b>590.GE2506</b>	1/5		
	8P			<b>590.EL2508</b> <sup>1</sup>	1/5	<b>590.GE2508</b> <sup>1</sup>	1/5		
	2P	Y1	105x150x82mm	<b>590.EL3212</b>	1/12	<b>590.GE3212</b>	1/12		
	3P			<b>590.EL3213</b>	1/12	<b>590.GE3213</b>	1/12		
32A	4P	Y1	105x150x82mm	<b>590.EL3214</b>	1/12	<b>590.GE3214</b>	1/12		
	3P+N			<b>590.EL3215</b> <sup>1</sup>	1/12	<b>590.GE3215</b> <sup>1</sup>	1/12		
	6P			Y3	155x210x107mm	<b>590.EL3206</b>	1/5	<b>590.GE3206</b>	1/5
	8P					<b>590.EL3208</b> <sup>1</sup>	1/5	<b>590.GE3208</b> <sup>1</sup>	1/5
40A	2P	Y1	105x150x82mm	<b>590.EL4012</b>	1/12	<b>590.GE4012</b>	1/12		
	3P			<b>590.EL4013</b>	1/12	<b>590.GE4013</b>	1/12		
	4P			<b>590.EL4014</b>	1/12	<b>590.GE4014</b>	1/12		
	3P+N	<b>590.EL4015</b> <sup>1</sup>	1/12	<b>590.GE4015</b> <sup>1</sup>	1/12				
	6P	Y3	155x210x107mm	<b>590.EL4006</b>	1/5	<b>590.GE4006</b>	1/5		
	8P			<b>590.EL4008</b> <sup>1</sup>	1/5	<b>590.GE4008</b> <sup>1</sup>	1/5		

<sup>1</sup> With late break and early make neutral pole

- Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
- Equipped with door interlock
- Break-through cable entries

1.5

