

ÎNTRERUPTOARE AUTOMATE COMBinate CU DIFERENȚIAL TIP AC 6 KA



5SU1356-1KK16

| Curent defect<br>$I_n$ (mA)   | Curent |        | Cod comandă |               |
|---|--------|--------|-------------|---------------|
|   | Un (V) | In (A) |             |               |
| C 6A  | 30     | 240    | 6           | 5SU1356-1KK06 |
| C 10A   |        |        | 10          | 5SU1356-1KK10 |
| C 16A   |        |        | 16          | 5SU1356-1KK16 |
| C 20A   |        |        | 20          | 5SU1356-1KK20 |
| C 25A   |        |        | 25          | 5SU1356-1KK25 |
| C 32A   |        |        | 32          | 5SU1356-1KK32 |
| C 40A   |        |        | 40          | 5SU1356-1KK40 |
| C 6A  | 300    | 240    | 6           | 5SU1656-1KK06 |
| C 10A   |        |        | 10          | 5SU1656-1KK10 |
| C 16A   |        |        | 16          | 5SU1656-1KK16 |
| C 20A   |        |        | 20          | 5SU1656-1KK20 |
| C 25A   |        |        | 25          | 5SU1656-1KK25 |
| C 32A   |        |        | 32          | 5SU1656-1KK32 |
| C 40A   |        |        | 40          | 5SU1656-1KK40 |
| Piesă necesară pentru a monta<br>contacte auxiliare 5ST3010 pe 5SU<br>(1 set = 5 buc) |        |        |             | 5ST3805-1     |